

THE ACECO PORTA-WASH STATION



The portable unit includes a GFI protected 4 gallon water heater that features a 1440W element, drawing only 12 amps at 120v.

Standard features include a stainless steel sink, gooseneck faucet, C-fold towel dispenser, piped drain with garden hose adapter, gallon bottle, pump & bracket. Fully assembled and ready to use.



#101T Porta-Wash Station with 4 Gallon Water Heater, 2 Handle Gooseneck Faucet w/ .35 GPM Aerator & Tempering Valve set at 105° F.

#102 Porta-Wash Station with 4 Gallon Water Heater, Single Sensor Gooseneck Faucet w/ .35 GPM Aerator & Tempering Valve set at 105° F.

OSHA GUIDELINE 1915.88e

#102 Single Sensor Faucet

#101T

Handwashing Facilities 1915.88(e) (1) The employer shall provide handwashing facilities at or adjacent to each toilet facility. 1915.88(e)(2) The employer shall ensure that each handwashing facility:1915.88(e)(2)(i) Is equipped with either hot and cold or lukewarm running water and soap, or with waterless skin-cleansing agents that are capable of disinfecting the skin or neutralizing the contaminants to which the employee may be exposed; and 1915.88(e)(2)(ii) If the facility uses soap and water, it is supplied with clean, single-use hand towels stored in a sanitary container and a sanitary means for disposing of them, clean individual sections of continuous cloth toweling, or a hand-drying air blower.