


HANGERS

HANGER, ADJUSTABLE SWIVEL RING, RUBBER LINED



- Rubber lined for copper pipe.
- Corrosion resistant.
- Provides sound and vibration isolation.
- Mounts on 3/8" threaded rod.
- 360 degree movement allows for mounting from wall, ceiling or floor.
- Height adjustable.
- Fast & Easy installation.
- Temperature rating -50 F to + 220 F.
- Moisture proof.

MATERIAL: Carbon steel

FINISH: Zinc Plated

APPLICATION: Suspending non-insulated copper tubing or pipe.

PART NO. GALV.	PIPE CPS	ROD	MAX. LOAD (Lbs.)	CARTON QUANTITY	WT./ CTN. (Lbs.)
SRR-12-5	1/2"	3/8"	400	100	10
SRR-34-5	3/4"	3/8"	400	100	10
SRR-100-5	1"	3/8"	400	100	13
SRR-114-5	1-1/4"	3/8"	400	100	14
SRR-112-5	1-1/2"	3/8"	400	100	15
SRR-200-5	2"	3/8"	400	100	17
SRR-212-5	2-1/2"	3/8"	600	50	9
SRR-300-5	3"	3/8"	600	50	9
SRR-400-5	4"	3/8"	1000	20	6

HANGER, ADJUSTABLE SWIVEL RING, FELT LINED



- Felt lined for copper pipe.
- Corrosion resistant.
- Provides sound and vibration isolation.
- Mounts on 3/8" threaded rod.
- 360 degree movement allows for mounting from wall, ceiling or floor.
- Height adjustable.
- Fast & Easy installation.

MATERIAL: Carbon steel.

FINISH: Zinc plated.

APPLICATION: Suspending non-insulated copper tubing or pipe.

PART NO. GALV.	PIPE CPS	ROD	MAX. LOAD (Lbs.)	CARTON QUANTITY	WT./ CTN. (Lbs.)
SRF-12-5	1/2"	3/8"	400	100	10
SRF-34-5	3/4"	3/8"	400	100	10
SRF-100-5	1"	3/8"	400	100	13
SRF-114-5	1-1/4"	3/8"	400	100	14
SRF-112-5	1-1/2"	3/8"	400	100	15
SRF-200-5	2"	3/8"	400	100	17
SRF-212-5	2-1/2"	3/8"	600	50	9
SRF-300-5	3"	3/8"	600	50	9
SRF-400-R	4"	3/8"	1000	20	6

HANGER, RUBBER LINED, SOUND ISOLATION