




# VALUE-WELL®

Value-Well pre-pressurized well tanks feature a deep-drawn steel dome design, butyl/EPDM diaphragm, 100% polypropylene liner, reliable hoop ring and groove construction and a 5-year limited warranty. Made in the USA at our ISO 9001:2008 registered facilities, Value-Well well tanks are an affordable solution.



| Sizing                            |  |           |           |                                       |           |            |
|-----------------------------------|--|-----------|-----------|---------------------------------------|-----------|------------|
| Pump Discharge Rate GPM (Approx.) | Pumps Up To 3/4 hp & 1 Minute Run Time |           |           | Pumps Over 3/4 hp & 2 Minute Run Time |           |            |
|                                   | 30/50 PSI                              | 40/60 PSI | 50/70 PSI | 30/50 PSI                             | 40/60 PSI | 50/70 PSI  |
| 5                                 | VW-20                                  | VW-20     | VW-20     | VW-34                                 | VW-34     | VW-44      |
| 7                                 | VW-32                                  | VW-32     | VW-32     | VW-44                                 | VW-62     | VW-62      |
| 10                                | VW-34                                  | VW-34     | VW-44     | VW-62                                 | VW-86     | VW-86      |
| 12                                | VW-44                                  | VW-44     | VW-62     | VW-86                                 | VW-86     | VW-119     |
| 15                                | VW-44                                  | VW-62     | VW-62     | VW-86                                 | VW-119    | VW-119     |
| 20                                | VW-62                                  | VW-86     | VW-86     | VW-119                                | VW-86 (2) | VW-86 (2)  |
| 25                                | VW-86                                  | VW-86     | VW-119    | VW-86 (2)                             | VW-86 (2) | VW-119 (2) |
| 30                                | VW-86                                  | VW-119    | VW-119    | VW-86 (2)                             | VW-119(2) | VW-86 (3)  |
| 35                                | VW-119                                 | VW-119    | VW-86 (2) | VW-119 (2)                            | VW-119(2) | VW-119 (3) |
| 40                                | VW-119                                 | VW-86 (2) | VW-86 (2) | VW-119 (2)                            | VW-86 (3) | VW-119 (3) |

**Larger Tank = Fewer Tank Cycles for Longer Tank and Pump Life**



| Specifications |                       |                               |                     |                   |                                 |                           |           |           |                        |
|----------------|-----------------------|-------------------------------|---------------------|-------------------|---------------------------------|---------------------------|-----------|-----------|------------------------|
| Model Number   | Tank Volume (Gallons) | Max. Accept. Volume (Gallons) | A Diameter (Inches) | B Height (Inches) | System Connection NPTF (Inches) | System Drawdown (Gallons) |           |           | Shipping Weight (lbs.) |
|                |                       |                               |                     |                   |                                 | 30/50 PSI                 | 40/60 PSI | 50/70 PSI |                        |
| VW-20          | 20                    | 11.4                          | 15                  | 32                | 1                               | 6.8                       | 5.9       | 4.7       | 33                     |
| VW-32          | 32                    | 11.2                          | 15                  | 47                | 1                               | 10.9                      | 9.4       | 7.6       | 43                     |
| VW-34          | 34                    | 34.0                          | 22                  | 30                | 1¼                              | 11.6                      | 10.0      | 8.0       | 61                     |
| VW-44          | 44                    | 33.9                          | 22                  | 36                | 1¼                              | 15.0                      | 12.9      | 10.4      | 69                     |
| VW-62          | 62                    | 34.1                          | 22                  | 47                | 1¼                              | 21.1                      | 18.2      | 14.6      | 92                     |
| VW-86          | 86                    | 46.4                          | 26                  | 47                | 1¼                              | 29.2                      | 25.3      | 20.3      | 123                    |
| VW-119         | 119                   | 46.4                          | 26                  | 62                | 1¼                              | 40.5                      | 35.0      | 28.1      | 166                    |

Malleable Iron System Connection.  
 Maximum Operating Temperature: 200°F. Factory Pre-Charge: 38 PSI. Maximum Working Pressure: 90 PSI.



1400 Division Road, West Warwick, RI 02893 USA  
 T: 800.426.8765 F: 800.293.1519  
[www.amtrol.com](http://www.amtrol.com)