

# SHC Flexible Fixture Hangers

## Outlet Box Mounted Series

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.

### Applications

- Designed for suspension of HID, fluorescent and incandescent lighting fixtures.
- SHC fixture hanger covers for mounting to 3-1/4" and 4" octagonal boxes and 4" square boxes.

### Features

- Protect fixture against wind and vibration damage.
- Cushion type for added protection where lighting fixtures are subjected to vibration.
- Ball type swivel joint permits 20° swing from vertical.
- Support fixtures with a maximum weight of 50 lbs/22.7 kg.

### Standard Materials

- Steel and malleable iron

### Standard Finishes

- Malleable iron and steel parts: zinc electroplate and clear chromate

### Certifications and Compliances

- CSA Certified: 065180
- UL Listed: E2527
- UL Standard: 514A

### Related Products

- For steel boxes, see *Commercial Products* section.



8438R



8458R

### Illustrated Features



Ball Type Swivel Fixture Hanger Covers shown with octagonal and with square stamped steel outlet boxes.

Lighting

LIGHTING: FLEXIBLE FIXTURE HANGERS – ORDINARY LOCATION

	Fixture Stem Size (Inches)	Length A in/mm	Support Weight (lbs/kg)	Catalog Number
<b>SHC Ball Type Swivel Hanger Covers – Permit 20° swing from vertical</b>				
<b>For 3-1/4" and 4" Octagonal Boxes</b>				
	1/2	1.75/44.5	50/22.5	<b>8438R</b>
	3/4	2.00/50.8	50/22.5	<b>8436R</b>
<b>For 4" Square Boxes</b>				
	1/2	1.75/44.5	50/22.5	<b>8458R</b>
	3/4	2.00/50.8	50/22.5	<b>8456R</b>