

Non-Metallic FR Series Device & Fixture Boxes



FR101F



FR405F



FR420F


Extra-wide flanges prevent water and air intrusion, no need for gaskets or caulking. Use for mounting coach lights on stucco and/or flat siding. For new construction.

FEATURES AND BENEFITS


- Converts FAST for use on any cladding system up to 1-7/8"!
- Ships pre-assembled, ready for use with 1-3/8" finish or cladding thicknesses
- Easily converts for 5/8" finish thicknesses by removing back and reinstalling on the opposite side
- Add extension ring for 7/8" thickness
- Extra-wide flanges help meet the International Energy Conservation Code by creating a protective barrier against air and water infiltration. No gaskets or caulking required.
- Large 20 cubic inch volume
- Made of high strength polycarbonate
- Wall mount—one-piece design for new installations
- Up to a 10 lb fixture rating

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	APPLICATION	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
FR101F	12680	Device Box	10	10	7.875	7.125	3.750	3.525
FR405F	12681	Pan Box	10	10	6.750	6.750	4.000	1.375
FR420F	09615	Fixture Box	10	10	6.750	6.750	4.000	1.986

PATENTED.



ASSEMBLY OPTIONS




Flange of box can be offset locating back panel to opposite side of box, as shown.

INSTALLATION INSTRUCTIONS

- For 5/8" wall finish thickness, loosen two screws and remove back.
- Re-install the back on the OPPOSITE side of the box.
- Assembled for 5/8" finish thickness.
- For 7/8" wall finish thickness, install the 1/4" extension ring
- ...to the front of the box.

For New Construction

Install FR series box BEFORE



or AFTER weather barrier house wrap

