Fan & Fixture Mounting Box with Adjustable Brackets for New Construction



FBX900 INCLUDES...

Expandable brackets with mounting screws, screws to adjust box position, mounting block with builtin electrical box, installed NM94 cable connector, and two parked-in-place fan/ fixture bracket installation screws (ready for installer).



Remove and use these

Loosen these

brackets and

position box

between rafters

screws to expand

screws to attach bracket ends to rafters



"Tooth" holds

temporarily in

place on rafter

brackets



For proper fan/fixture installation, use supplied template to level and position brackets between rafters. Remove captive screws on sides of brackets and use to attach FBX900 assembly to rafters.



Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.

Loosen the screws noted in first illustration. Slide box to center it between rafters. Tighten screws. Install wires.

3

Adjustable from 1'-2" to 2'-0"



around the box. (Note: captive screws in box.) Install fan or fixture per manufacturer's instructions using captive installation screws.

FEATURES AND BENEFITS

centering within room.

- Expandable brackets hold box securely between joists-no need to cut and nail 2x4s to center the fan or fixture
- Allows fans/fixtures to be perfectly centered within room
- Large, 8" square mounting surface handles newer fans with larger canopies
- No loose parts to misplace-totally self-contained!
- Installs quickly and securely
- Includes a template to level and position brackets between rafters
- Taller sides fit cathedral ceilings with angles greater than 80°
- Paintable, textured finish

PATENTED.

- Fan/fixture installation screws are parked...ready for easy fan/fixture bracket installation!
- UL rated: 70 lb fan/fixture; CSA rated: 50 lb fan/fixture

CATALOG	UPC/DCI/NAED	DESCRIPTION	UNIT	STD	DIM	DIM
NUMBER	MFG #018997	/ CU. IN.	PKG	PKG	A	B
FBX900	75224	Adjustable. Fits Cathedral Ceilings 80° or Greater / 14.5 Cu. In.	1	1	2.300	13.200

For fan/fixture box information, refer to FB900 on page R-16. Refer to chart on page R-22 for load ratings and number of single conductors.

