Combination Type T



Units have a threaded interior for use with rigid or IMC as well as set screws for use with EMT. Preassembled with cover and neoprene gasket. NPT Threads. NEMA TYPE 2,3,3R & 4.

c 🖫 us File No. E11077

🕛 Listed Raintight when used with rigid conduit.

Aluminum with Cover and Gasket

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
T-41CGC	1/2"	10	60
T-42CGC	3/4"	10	60
T-43CGC	1"	5	30
T-44CGC	1 1/4"	2	10
T-45CGC	1 1/2"	2	10
T-46CGC	2"	1	6

Service Entrance LB

Allows access to the interior of a conduit system for inspection, pulling and maintenance. Mounts flush against structure. Raintight. NPT Threads. Neoprene gasket. NEMA TYPE 2,3,3R & 4.



(h) File No. E11077

Aluminum

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.	Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
1025	1/2"	5	50	1029	1 1/2"		5
1026	3/4"	5	50	1030	2"		4
1027	1"		20	1028-XL	1 1/4"		10
1028	1 1/4"		10	1030-XL	2"		6

Sill Plates



When used with sealing compound,

sill plates prevent water from entering structure.

Aluminum

With Screws and Sealing Compound

Catalog	Service	Unit	Std.
Number	Cable Size	Qty.	Pkg.
938-C	3 - 2	10	100

PVC Without Screws and Sealing Compound

Catalog	Service	Unit	Std.
Number	Cable Size	Qtv.	Pkg.
938-PVC	3 - 4 to 3 - 0	10	100

Service Entrance LB



Allows access to the interior of a conduit system for inspection, pulling and maintenance. Mounts flush against structure, raintight. NPT Threads. Neoprene gasket. NEMA TYPE 2,3,3R & 4.

(h) File No. E11077

Aluminum

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
1025	1/2"	5	50
1026	3/4"	5	50
1027	1"		20
1028	1 1/4"		10
1029	1 1/2"		5
1030	2"		4
1028-XL	1 1/4"		10
1030-XL	2"	1	6