



Extra-Long Zinc Die Cast Raintight Compression Connectors

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. Extra-long threads for connecting to thicker enclosures and solar combiner boxes. Patented.

cULus File No. E24001

Catalog Numbers	Trade Sizes
250-RT2XL thru 252-RT2XL	1/2" thru 1"



Zinc Die Cast Raintight Compression Couplings

Compression style coupling used to join two lengths of EMT. Internal sealing rings create a raintight seal. Patented.

UL File No. E24001

Catalog Numbers	Trade Sizes
260-RT thru 269-RT	1/2" thru 4"



Mighty-Merge® Zinc Die Cast Raintight Combination Couplings

Couplings used to transition EMT to rigid for a secure raintight/wet location seal. Patented.

cETLus Listed

Catalog Numbers	Trade Sizes
290-RT thru 292-RT	1/2" thru 1"



Straight Zinc Die Cast Liquid Tight Connectors

Use with metallic and nonmetallic "Type B" liquid tight conduit. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

UL File No. E9391

CSA File No. LR39354

Catalog Numbers	Trade Sizes
429-LT2 thru 439-LT2	3/8" thru 4"
(90°C Insulated Throat) 429-LT12 thru 439-LT12	3/8" thru 4"



90° Zinc Die Cast Liquid Tight Connectors

Use with metallic and nonmetallic "Type B" liquid tight conduit. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

UL File No. E9391

CSA File No. LR39354

Catalog Numbers	Trade Sizes
469-LT2 thru 479-LT2	3/8" thru 4"
(90°C Insulated Throat) 469-LT12 thru 479-LT12	3/8" thru 4"



Zinc Die Cast UF Connectors

Connector provides watertight seal around underground feeder cable. Tapered (NPT) threads.
UL File No. E11698

Catalog Numbers	Trade Sizes	Cable Size
761-UF	1/2"	14/2 (.250") to 10/2 (.500")
762-UF	3/4"	14/3 (.260") to 10/3 (.720")



Zinc Die Cast Watertight Service Entrance Cable Connectors

Compression type connector which provides watertight seal around service entrance cable.

Catalog Numbers	K.O. Size	Grommet Opening Size
763-4	1"	.520" x .840"
763-6	1"	.440" x .700"
763-8	1"	.406" x .688"
764-2	1 1/4"	.600" x 1.000"
764-2N	1 1/4"	.665" x 1.094"
764-3	1 1/4"	.560" x .950"
765-2	1 1/2"	.865" x 1.325"
765-3	1 1/2"	.875" x 1.375"
766-2	2"	.860" x 1.340"
766-3	2"	.870" x 1.370"
766-4	2"	.900" x 1.500"
766-4N	2"	1.100" x 1.750"



Mighty-Seal® Zinc Die Cast Jacketed MC and TECK Cable Connectors

Used for connecting Jacketed Cable (parking deck/lot cable) to boxes or enclosures. Patented.
cULus File No. E20534

Catalog Numbers	K.O. Size	MC Cable Range	TECK Cable Range
595-DC2	1/2"	12/2 - 10/3	14/2 - 12/2
595-DCI2*	1/2"	12/2 - 10/3	14/2 - 12/2
596-DC2	1/2"	10/4 - 8/3	14/3 - 10/3
596-DCI2*	1/2"	10/4 - 8/3	14/3 - 10/3
895-DC2	1/2"	12/2 - 10/3	14/2 - 12/2
895-DCI2*	1/2"	12/2 - 10/3	14/2 - 12/2

*105°C Insulated Throat



Combination Couplings

Coupling used to join either metallic or nonmetallic (Type "B") liquid tight to EMT. Concrete-tight. UL Listed "Raintight".

UL File No. E24001: 4360-DC and 4361-DC
CSA File No. LR39354: 4360-DC and 4361-DC
cULus File No. E24001: 4262-DC thru 4365-DC

Catalog Numbers	Trade Sizes
4360-DC thru 4365-DC	1/2" thru 2"