



Extra-Long Zinc Die Cast Raintight Compression Connectors

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. Extra-long threads for connecting to thicker enclosures and solar combiner boxes. Patented.

cULus File No. E24001

Catalog Numbers	Trade Sizes
250-RT2XL thru 252-RT2XL	1/2" thru 1"



Zinc Die Cast Raintight Compression Couplings

Compression style coupling used to join two lengths of EMT. Internal sealing rings create a raintight seal. Patented.

UL File No. E24001

Catalog Numbers	Trade Sizes
260-RT thru 269-RT	1/2" thru 4"



Mighty-Merge® Zinc Die Cast Raintight Combination Couplings

Couplings used to transition EMT to rigid for a secure raintight/wet location seal. Patented.

cETLus Listed

Catalog Numbers	Trade Sizes
290-RT thru 292-RT	1/2" thru 1"



Straight Zinc Die Cast Liquid Tight Connectors

Use with metallic and nonmetallic "Type B" liquid tight conduit. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

UL File No. E9391

CSA File No. LR39354

Catalog Numbers	Trade Sizes
429-LT2 thru 439-LT2	3/8" thru 4"
(90°C Insulated Throat) 429-LT12 thru 439-LT12	3/8" thru 4"



90° Zinc Die Cast Liquid Tight Connectors

Use with metallic and nonmetallic "Type B" liquid tight conduit. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

UL File No. E9391

CSA File No. LR39354

Catalog Numbers	Trade Sizes
469-LT2 thru 479-LT2	3/8" thru 4"
(90°C Insulated Throat) 469-LT12 thru 479-LT12	3/8" thru 4"



Straight Steel and Malleable Iron Liquid Tight Connectors

For use with metallic liquid tight conduit. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

Steel: 429-SLT thru 432-SLT

Malleable Iron: 433-SLT thru 441-SLT

cULus File No. E9391: 436-SLT thru 439-SLT

UL File No. E9391: Steel and 436-SLTI thru 439-SLTI

CSA File No. LR39354: Steel

Note: UL Listing not applicable to 5" & 6" Malleable Iron

Catalog Numbers	Trade Sizes
429-SLT thru 441-SLT	3/8" thru 6"
(105°C Insulated Throat)	
429-SLTI thru 441-SLTI	3/8" thru 6"



Polyolefin-Coated Straight Steel and Malleable Iron Liquid Tight Connectors

Straight connector for use with metallic and nonmetallic "Type B" liquid tight conduit.

Consult Factory for Listings and Availability.

Catalog Numbers	Trade Sizes
429-SLTC thru 439-SLTC	3/8" thru 4"



Made in the USA Straight Steel and Malleable Iron Liquid Tight Connectors

For use with metallic liquid tight conduit. Zinc Electroplated. Suitable for use in Class 1, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B).

UL File No. E9391

Catalog Numbers	Trade Sizes
429-SLTUS thru 439-SLTUS	3/8" thru 4"
(105°C Insulated Throat)	
429-SLTIUS thru 439-SLTIUS	3/8" thru 4"

