

Current-Carrying Hoses



Lightweight, Crushproof

CH615

This lightweight, Current-Carrying direct-connect hose springs back to retain original shape. Features a 3-position on-off switch. Available in dark gray.

- Recommended for use with NuTone CI358 and CI390 series electrified inlets
- For use with NuTone CT700 Deluxe Electric Power Brush
- UL approved



CH515

This lightweight, Current-Carrying corded hose springs back to retain original shape. Features a 3-position on-off switch and 6 ft. line cord. Available in dark gray.

- For use with NuTone CT700 Deluxe Electric Power Brush
- Includes patent pending Universal hose end which fits all NuTone and most other standard inlets
- UL approved

Hose Accessories



CA130

A hose sock can help prevent scratching corners of walls and marking furniture as you move from room to room while vacuuming.



Hose Selection Chart

Model No.	Description	Hose Length	Inside Diameter	Power Head Switch	Power Unit Switch	Color
372	Low Voltage Utility/Garage Hose	32'	1-1/4"	No	No	Dark Gray
CH230L	Low Voltage Standard Hose	42'	1-3/8"	No	Yes	Dark Gray
CH235	Crushproof Low Voltage Hose	30'	1-3/8"	No	Yes	Dark Gray
CH515	Current-Carrying Crushproof Hose w/Status Indicator Light	30'	1-1/4"	Yes	Yes	Dark Gray
CH615	Direct-Connect Crushproof Hose w/Status Indicator Light	30'	1-1/4"	Yes	Yes	Dark Gray

Hose Accessories

Model No.	Description	Hose Length	Inside Diameter	Color
CA130	Hose Sock	30' – 32'	1" & 1-3/8" dia. Hoses	Gray

Electrified Direct Connect Inlets



Electrified Inlets make it a simple one-step operation to plug in a Current-Carrying hose – no 120V extension cord to carry around. Compatible with NuTone CH615.

CI390 Standard

The ElectraValve® Electrified Inlet operates on standard house wiring. It eliminates the need for the extension of electrical cords from the inlet to an electrical outlet. The molded power receptacle clips to a mounting plate and the housing wire is run to the nearest outlet box.

- UL listed Assembly
- Standard:
 - CI390W** – White
 - CI390V** – Ivory

CI395RK Rough-In Kit

The Electrified Inlet Rough-In Kit includes everything you need to install the CI390. Includes mounting plate, snap-in power receptacle, 6' of 12-gauge cable assembly, plaster guard, CF382S elbow and mounting screws for plaster guard.

CI358 Supervalves

The Supervalve Electrified Inlet operates on standard house wiring. Includes wall valve, rough-in plate with junction box and strain relief.

- UL listed assembly
- Standard:
 - CI358W** – White
 - CI358IV** – Ivory

HOSE-INLET COMPATIBILITY:

		Inlet Type					
		CI390	CI358	360	330	CF372	
Hose Type	Current Carrying	CH615	•	•		•	
		*CH515	◦	◦	•	•	
		372		◦	◦	•	
Low Voltage		CH235	◦	•	•	◦	
		CH230L	◦	◦	•	•	
Garage Kits		CK140		◦	◦	•	
		CK145		◦	◦	•	

* Includes 6 ft. line cord

◦ Limited Function (suction only/non-powered)

• Full Function