



Bottom Turn Knob Lampholders

660W 250V

Bottom Turn Knob Lampholders

FEATURES


- Molded of high-temperature thermoset plastic.
- Screw terminals are backed out - ready for wiring.

Medium Base Lampholders - Phenolic Body



Rating	Nipple	Bracket	Finish -		
W	V	Description	Length	Nipple & Nuts	
660	250	0.375" (9.53mm) 1/8-27 Nipple with Removable Knob	0.375" (9.53mm)	0.69" (17.46mm)	Nickel 1198

Panel Cutout - Bottom Turn Knob



R-11 Lampholders



Incandescent Lampholders

250W 250V
660W 250V

Incandescent Lampholders

FEATURES

- Screw terminals are backed out - ready for wiring.
- Interiors have removable turn knobs.
- Hickeys and nipples are threaded for mounting on standard fixture, lamp stems or brackets.

Incandescent Medium Base Fixture Sockets

Rating	Bracket	Overall	
W	V	Description	Switch
660	250	Porcelain - Screw Terminals	Keyless
660	250	Phenolic - Screw Terminals	Keyless

Electrolier Medium Base Sockets 0.13" (3.18mm) - IPS Bracket - Screw Terminals

Rating	Bracket	Overall	
W	V	Description	Switch
250	250	One Circuit	Turn Knob
250	250	Two Circuit (3-Way)	Turn Knob

*Not NOM certified
†Not UL

TESTING & CODE COMPLIANCE

- UL Listed, file E7430, UL 496 requirements
- CSA Certified, file 1739 (6231-07), Meet CSA requirements, C22.2 no. 43
- NOM Certified

MATERIAL CHARACTERISTICS

Temperature Rating: -40°C to 65°C

