



Connectivity Points

In today's homes, service connection points are nearly as important as media distribution itself. Finish off service connection points with wallplates that give you the flexibility and style you need. Decorator inserts upgrade connection points to a designer look, come in a variety of configurations and are compatible with any decorator wallplate.

Connectivity Point Families



Decorator Inserts with
Connectors

D-12



Standard Size Wallplates
with Connectors

D-13



Mid-Size Wallplates
with Connectors

D-13

Connectivity Point Colors

Almond
(A)

Black
(BK)

Gray
(GY)

Ivory
(V)

Light Almond
(LA)

White
(W)

Decorator Inserts With Connectors

Mounting Strap Jacks & Adapters
Category 3 RJ11, RJ14
Coax Type F



2162



3560-4



3562

Features

- Flush mount telephone jacks for use in Category 3 RJ11 & RJ14 applications
- Type F Coaxial jack ideal for use with cable, satellite, TVs, DVDs, video applications and outdoor antennas
- 100% computer-tested to assure consistent high quality and reliable performance
- Fits in standard decorator wallplate openings

Decorator Mounting Strap Inserts With Connectors



Description	Color Suf	Catalog No.
Single Type F Coaxial Adapter, Decorator Insert	A, BK, LA, V, W	□ 2162__
Single 4-Conductor Telephone Jack, Decorator Insert Type 625 Screw Terminals	A, LA, V, W	□ 3560-4__
Combination Telephone Jack & Coaxial Adapter, Decorator Insert, One 4-Conductor Phone Jack, One Type F Coax Jack	A, LA, V, W	□ 3562__

cULus Listed to UL1863, file no. E142334; FCC part 68 requirements

Color Ordering Information:

For ordering devices, include Catalog No. followed by the Color Suffix: A (Almond), BK (Black), LA (Light Almond), V (Ivory), W (White)

A	BK	LA	V	W
(Almond)	(Black)	(Light Almond)	(Ivory)	(White)

Specification Information: Please visit www.cooperwiringdevices.com.
Specifications and availability are subject to change without notice.

Flush Mount Telephone Jacks



Flush Mount Telephone Jacks

FEATURES

- Spring wire contacts with 50 micro-inches gold plating over nickel measure 0.018" (0.005mm) diameter to maximize contact life and reduce corrosion.
- For use in Category 3 RJ11, RJ14 and RJ25 applications.
- All telephone jacks with wallplates are box mounting.
- 100% computer-tested to assure consistent high quality and reliable performance.
- Terminals are color-coded for easy wiring.

Telephone Jack – Decorator – 4 Conductor – RJ11, RJ14 Applications

Description	Color	Catalog No. UL Version
Type 625 Screw Terminals	Almond	3560-4A
	Ivory	3560-4V
	Light Almond	3560-4LA
	White	3560-4W

Jack – Decorator – 6 Conductor – RJ11, RJ14, RJ25 Applications


Description	Color	Catalog No.
Type 625 Screw Terminals	Almond	3560-6A
	Ivory	3560-6V
	Light Almond	3560-6LA
	White	3560-6W

Two Jacks with Wallplate – 4 Conductor – RJ11, RJ14 Applications


Description	Color	Catalog No.	
		Non-UL Version	UL Version
Type 625B3 Screw Terminals	Almond	–	3546-4A
	Ivory	2546-4V	3546-4V
	Light Almond	–	3546-4LA
	White	2546-4W	3546-4W

Two Jacks with Wallplate – 6 Conductor – RJ11, RJ14, RJ25 Applications

Description	Color	Catalog No.
Type 625B3 Screw Terminals	Almond	3546-6A
	Ivory	3546-6V
	Light Almond	3546-6LA
	White	3546-6W



3560-4



3546-4

COMMERCIAL
RESIDENTIAL

H-4
COMMUNICATIONS
PREMISE WIRING
PRODUCTS

TESTING & CODE COMPLIANCE

- Meets UL requirements (file no. E134135).
- CSA Certified (file no. 090192-0-0000)

MATERIAL CHARACTERISTICS

Self-extinguishing high-impact thermoplastic meets UL 94, V0 flame retardancy rating.