



# Commercial Specification Grade Straight Blade Power Devices

4 Pole, 4 Wire Non-Grounding  
NEMA 18-60,  
60A 3ØY 120/208V  
Wallplate Guide

## Power Devices

### FEATURES

- Heavy gauge steel mounting strap zinc-plated for corrosion resistance.
- Receptacles for use with copper or aluminum wire.
- High strength glass reinforced nylon body resist breakage in high abuse areas for Cat. No. 5515N.

INDUSTRIAL  
COMMERCIAL  
RESIDENTIAL

## A-29 STRAIGHT BLADE RECEPTACLES

### TESTING & CODE COMPLIANCE

- UL file:
- Receptacles:  
(file no. E15058;  
19: UL and cUL,  
(file no. E15012)
- CSA (file no. 6914  
(6233-01)).
- Meets all CSA requirements,  
C22.2 no. 42,
- NOM Certified,  
except as noted,

### MATERIAL CHARACTERISTICS

Meets flammability requirements per UL 94,  
5515N: V2 rated.  
Temperature Rating:  
-20°C (without impact) to 75°C max. continuous.  
5515N:  
-40°C (without impact) to 105°C max. continuous.



**1169**



**19**

### NEMA 18-60 Rating 60A 3ØY 120/208V

#### Receptacles

Description	Color	Catalog No.
Flush	Black	5515N*
On 4.6875" (119.06mm) Steel Cover	Black	1169*
Panel Mount	Black	59

\*Not CSA or NOM

#### Plugs

Description	Color	Catalog No.
Angle - Plastic	Black	19

### Wallplate Guide for Power Devices

Power Device Catalog No.	Wallplate Catalog No.
32, 38, 1233, 1234, 1253, 1254, 1257, 1258, 1263, 5700N, 5709N, 5716N, 5795N, 7985N	39CH, 68, 2068, 2168, 5068, 93221, 93227
5515N, 5744N, 5754N, 8430N, 8450N, 8460N, 9460N	69, 5169, 93223
122	192



**18-60R**



**18-60P**