# Combination devices



## Decorator heavy duty grade combination devices

#### **Product description**

Single-pole, 3-way 15A, 120V/AC switches 15A, 125V receptacles



5-15R





TR7730

## **Design features**

- 120/277V/AC rating ideal for fluorescent lighting fixtures and a broad variety of applications
- Switches are horsepower rated for motor loads per UL 20
- · Thermoplastic rocker, top and backbody are virtually unbreakable to deliver years of durable performance
- · Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant
- · Steel mounting strap is zinc-plated for added corrosion resistance
- · Convenient patented built-in wire stripper speeds installation
- · Backwire clamps on side terminals provide for easy installation of #12 and #14 AWG wire
- · Triple wipe blade contacts and double wipe ground contacts to insure long-term plug retention (TR7730)
- Tri-combo screw heads offer greater installation flexibility

#### **Decorator combination switches**









Rating					
Α	V/AC	Description	Color suffix	Catalog no.	
600	120	Two single-pole switches, back & side wire	A, BK, LA, V, W	□ 7728	
600	120	Three single-pole switches, back & side wire	A, BK, LA, V, W	□ 7729	
1000	120	Two 3-way switches, back & side wire	A, BK, LA, V, W	□ 7731	
1000	120	One single-pole switch w/ one 3-way switch, back & side wire	A, BK, LA, V, W	□ 7732	

cULus Listed to UL20, file no. E18704; NOM certified

#### Decorator combination switch with receptacle







Α	V/AC	Description	Color suffix	Catalog no.
15	120	One single-pole switch with	A, BK, LA, V, W	□ TR7730
15	125	one tamper resistant NEMA 5-15R receptacle, back & side wire		
cULu	ıs Listed to UL	.20, file no. E18704; NOM certified		

## Horsepower rated for motor loads per UL 20

	Rating			
Α	120V/AC	240V/AC	Max. Amps	
15	1/2 HP	2 HP	12	

## **Color ordering information:**

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), BK (Black), LA (Light Almond), V (Ivory), W (White).



Dimensional information: B-68 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.



Tamper resistant