The Eaton difference

- Extra durability Heavy Duty Grade models available for high abuse areas
- · Screw-Catch feature on traditional duplex devices automatically holds the wallplate mounting screw in place
- Built-in wire looper to speed termination of both #14 and #12 AWG wire
- · Slotted, Phillips and Robertson Tri-combo screw heads offer greater installation flexibility
- Tamper Resistant versions provide compliance with 2014 NEC[®] section 406.12 and provide significantly improved protection over traditional receptacles with removable plastic safety caps



SECTION

Specific receptacle solutions for today's needs



www.eaton.com www.cooperwiringdevices.com See page B-27



EATON 2014 Residential Buyers Guide



Receptacles

CO/ALR standard grade receptacles

Product description

2-pole, 3-wire grounding 15A, 125V/AC

Design features

- · For direct connection to aluminum or copper wire
- Double-wipe ground contacts ensure long-term ground retention
- Combination Slotted/Phillips head mounting and terminal screws for installation flexibility

CO/ALR duplex receptacles

- Easy access split circuit break-off tab
- Terminal screws backed out and ready for wiring
- Side wire terminals accept up to #10 solid copper wire or solid aluminum wire

| A | v/AC | Description | Color suffix | Catalog no. | |
|----|------|--|--------------|-------------|---|
| 15 | 125 | NEMA 1-15R duplex receptacle, non-grounding, side wire | V, W | □ 5270 | • |

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: V (Ivory), W (White).

| v | w |
|---------|---------|
| (Ivory) | (White) |

Dimensional information: B-68 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21







⊂G

5-15R