


## Heavy duty grade receptacles

### Product description

2-pole, 3-wire grounding  
15A, 125V/AC  
20A, 125V/AC



TRCR20



TR6250



1877

### Design features

- Heavy duty grade receptacles are designed and built for heavier use and feature enhanced ground contacts
- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant
- Durable impact-resistant thermoplastic face and back body is virtually unbreakable and also chemical-resistant
- Side-wire terminals accept up to #10 AWG solid wire
- Screw-Catch feature on duplex devices speeds mounting of wallplates
- Galvanized steel wrap-around mounting strap for superior assembly security
- Patented built-in wire stripper for #12 and #10 AWG wire (except TRCR models) to speed installation
- Duplex and decorator devices feature automatic grounding system that eliminates the need for bonding jumper in grounded metal enclosures and provides a redundant measure of ground continuity where a jumper is used



### Heavy duty tamper resistant duplex receptacles



Rating	A	V/AC	Description	Color suffix	Catalog no.
15	120		Tamper resistant NEMA 5-15R duplex receptacle, side wire	A, B, BK, GY, LA, V, W	<input type="checkbox"/> TRCR15__
20	125		Tamper resistant NEMA 5-20R duplex receptacle, side wire	A, B, BK, GY, LA, V, W	<input type="checkbox"/> TRCR20__

cULus Listed to UL498, file no. E15058; NOM certified

### Heavy duty tamper resistant single receptacles



Rating	A	V/AC	Description	Color suffix	Catalog no.	
15	125		Tamper resistant NEMA 5-15R decorator single receptacle, side wire	B, BK, V, W	<input type="checkbox"/> TR6250__	•
15	125		Tamper resistant NEMA 5-15R single receptacle, side wire	A, B, BK, LA, V, W	<input type="checkbox"/> TR817__	
20	125		Tamper resistant NEMA 5-20R decorator single receptacle, side wire	LA, V, W	<input type="checkbox"/> TR6350__	
20	125		Tamper resistant NEMA 5-20R single receptacle, side wire	A, B, BK, LA, V, W	<input type="checkbox"/> TR1877__	

cULus Listed to UL498, file no. E15058; NOM certified

### Heavy duty single receptacles




Rating	A	V/AC	Description	Color suffix	Catalog no.	
15	125		5-15R Single receptacle, side wire	B, BK, LA, V, W	<input type="checkbox"/> 817__	•
20	125		5-20R Single receptacle, side wire	A, B, BK, LA, V, W	<input type="checkbox"/> 1877__	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White).



**Dimensional information:** B-68, B-69 **Specification information:** Please visit [www.cooperwiringdevices.com](http://www.cooperwiringdevices.com)  
**Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page F-21

Tamper resistant