


Range & dryer power receptacles

Product description

3-pole, 3-wire non-grounding
30A, 125/250V/AC
50A, 125/250V/AC


Design features

- For replacement use in older homes with 3-wire range and dryer connection points
- Heavy gauge galvanized steel mounting strap for corrosion resistance
- Flush receptacles fit one-gang or two-gang enclosures
- For use with copper or aluminum wire
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom




10-30R

10-50R



14-30R

14-50R



32B



112



1258

Flush power receptacles



Rating		Description	Color	Catalog no.	
A	V/AC				
30	125/250	NEMA 10-30R flush mount dryer power receptacle, matching plug S80	B	□ 38B	•
50	125/250	NEMA 10-50R flush mount range power receptacle, matching plug S80	B	□ 32B	•

cULus Listed to UL498 & UL943, file no. E60120; NOM certified

Surface power receptacles



Rating		Description	Color	Catalog no.	
A	V/AC				
30	125/250	NEMA 10-30R flush mount dryer power receptacle, matching plug S80	BK	□ 125	•
50	125/250	NEMA 10-50R flush mount range power receptacle, matching plug S80	BK	□ 112	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Flush power receptacles




Rating		Description	Color	Catalog no.	
A	V/AC				
30	125/250	NEMA 14-30R flush mount dryer power receptacle, matching plug S21	BK	□ 1257	•
50	125/250	NEMA 14-50R flush mount range power, matching plug S21	BK	□ 1258	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

B (Brown), BK (Black)



Dimensional information: B-70 **Specification information:** Please visit www.cooperwiringdevices.com


Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21

Range & dryer power receptacles

Product description

3-pole, 4-wire grounding
30A, 125/250V/AC
50A, 125/250V/AC



14-30R

14-50R



1212



58

Surface power receptacles



Rating		Description	Color	Catalog no.	
A	V/AC				
30	125/250	NEMA 14-30R surface mount dryer power receptacle, matching plug S21	BK	□ 1225	•
50	125/250	NEMA 14-50R surface mount range power receptacle, matching plug S21	BK	□ 1212	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Panel power receptacles



Rating		Description	Color	Catalog no.	
A	V/AC				
50	125	NEMA 14-50R panel mount range power receptacle, matching plug S21	BK	□ 58	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for flush power receptacles



Description	Color suffix	Catalog no.	
Thermoset 1-gang wallplate for one power receptacle	A, B, V, W	□ 2068__	•
Thermoset 2-gang wallplate for one power receptacle	A, B, LA, V, W	□ 2168__	•

Listed to UL498, file no. E15058

Compatible wallplates / standard size for flush power receptacles



Description	Color	Catalog no.	
1-gang wallplate for one power receptacle	Stainless Steel	□ 93221	•
2-gang wallplate for one power receptacle	Stainless Steel	□ 93227	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42

Compatible wallplates / standard size for flush power receptacles



Description	Color suffix	Catalog no.	
Nylon 1-gang wallplate for one power receptacle	V	□ 5068	•
Polycarbonate 1-gang wallplate of one power receptacle	B, BK, V, W	□ PJ724__	•
Polycarbonate 2-gang wallplate for one power receptacle	B, V, W	□ PJ703__	•

Listed to UL498, file no. E15058

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), Stainless Steel, W (White).



Dimensional information: B-70 **Specification information:** Please visit www.cooperwiringdevices.com
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21