Wallplate accessories

Wallplate accessories

Product description

GFCI extension ring, adapters, wallplate screws, blank insert & pilot light lamp holder

c (UL) us Wallplate accessories

Description	Material	Color suffix	Catalog no.		
GFCI extension ring for use with GFCI's, 7/8" spacer, cULus Certified	Polypropylene	B, BLK, LA, V, W	□ GFER	GFER	
Adapter—decorator to blank	Polypropylene	B, LA, V, W	□ 2160	•	
Adapter—decorator to toggle	Polypropylene	V, W	□ 2161	•	
Toggle & receptacle wallplate screws	Metal, baked enamel head	B, LA, V, W	□ 231		
#6-32 x 1/2"	Nylon	RD, V, W	□ 232		
Toggle & receptacle wallplate screws #6-32 x 5/16"		LA, V, W	□ 2231		

GFER: cULus Listed to UL514C, CSA certified to C22.2, no. 18-98

Sub-frame & blank insert

Description	Color suffix	Catalog no.
Blank insert and strap for any switch plate		□ 756

Louvered wallplate accessorie Description	Material	Catalog no.	4
Recessed pilot light lamp holder with 6 watt clear S-6 bulb	Polypropylene	□ 153	

Listed to UL496, file no. E18522; CSA certified to C22.2, no. 43

LED steplight

Product description

15A, 120V/AC

c(UL)us LED Steplight

Description	Color suffix	Catalog no.
15A, 120V/AC LED steplight, includes vertical & horizontal louvered wallplates	A, LA, W	□ 7739-BOX
chillus Listed to Lill 1598, file no. E328628: CSA certified to C22.2, no. 43		

s Listed to UL 1598, file no. E328628; CSA certified to C22.2, no. 43



GFER







756



153



7739-BOX

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White).

А	В	ВК	GY	LA	RD	v	w
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

Dimensional information: C-5, C-6 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21