




SECTION

Construction grade switches

Construction grade switches

Product description

Single-pole, double-pole
 3-way, 4-way
 15A, 120/277 V/AC
 20A, 120/277 V/AC



1201

Construction grade switch back and side wire



Rating		Description	Color suffix	Catalog no.
A	V/AC			
15	120/277	Single-pole toggle switch	B, GY, LA, V, W	□ 1201__
15	120/277	3-Way toggle switch	B, GY, LA, V, W	□ 1203__
20	120/277	Single-pole toggle switch	B, BK, GY, LA, RD, V, W	□ 1221__
20	120/277	Double-pole toggle switch	B, BK, GY, LA, RD, V, W	□ 1222__
20	120/277	3-Way toggle switch	B, BK, GY, LA, RD, V, W	□ 1223__
20	120/277	4-Way toggle switch	B, BK, GY, LA, RD, V, W	□ 1224__

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

B	BK	GY	LA	RD	V	W
(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

Specification information: 120/277V construction: E-36 **Testing & code compliance:** cULus Listed to UL 20, file no. 18704, NOM Certified.
Material characteristics: Environmental: Flammability meets UL 94 requirements, V2 rated. Temperature rating: -20°C to 60°C (-4°F to 140°F)
Compliances, specifications and availability are subject to change without notice.