

## Fluorescent lampholders

### Product description

Medium bi-pin  
660W, 600V/AC

### Features

- For replacement use in fluorescent lighting fixtures
- Captive pal nut for easy mounting
- Use for flush or surface mounting
- Push-in wire terminals feature release slots

### Fluorescent lampholders



Rating		Description	Color	Catalog no.
W	V/AC			
660	600	Standard, push wire, slide-on & screw switch	W	□ 2509W*
		Short, push wire, slide-on & screw switch	W	□ 2510W
		Standard, screw terminals, screw switch	W	□ 924W†

For panel cutout dimensional data, see Section Q-Technical Reference  
\*Not NOM certified, † Not UL Listed or CSA certified

## Pigtail lampholders

### Product description

Medium base  
660W, 250V/AC; 660W, 600V/AC

### Features

- For use in electrical equipment, harnesses, light strings and related applications
- Rubber sockets have an extended lip to seal against bulb
- Wire leads are 5" (127.0mm) of color-coded stranded wire, stripped 1" (25.4mm) for easy connection
- Metal shell interiors are aluminum, 145 nickel-plated copper with sealed leads where they enter husk

### Pigtail lampholders




Rating		Description	Catalog no.	
W	V/AC			
660	250	Phenolic, wire size #14 AWG	□ 722*	•
660	600	Weatherproof rubber, wire size #14 AWG	□ 145†	


For panel cutout dimensional data, see Section Q-Technical Reference  
\*Only UL Listed, † Not CSA certified



2509W



2510W



924W



722



145

### Color information:

W (White)



(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30