

## Canopy switches

### Product description

Single-pole, two-circuit  
 1A, 125V/AC; 1A, 250V/AC  
 3A, 125V/AC; 3A, 250V/AC; 6A, 125V/AC

### Features

- Wide variety of sizes for use in fixtures, appliances, doorways and equipment
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long
- Hex nut and finishing nut furnished
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm)




449NP



458BD



442



460



452

### Push button



Rating		Circuit	Description	Sequence	Finish	Catalog no.
A	V/AC					
1	125 "T"	Single pole	Metal push button	On-off	Nickel	<input type="checkbox"/> 449NP
1	250					
3	250					

### Pull chain



Rating		Circuit	Description	Sequence	Finish	Catalog no.
A	V/AC					
1	125 "T"	Single pole	Pull chain with end bell	On-off	Nickel	<input type="checkbox"/> 458NP
1	250					
3	125					
1	125 "T"	Single pole	Pull chain with end bell	On-off	Brass	<input type="checkbox"/> 458BD
1	250					
3	125					
3	125 "T"	Single pole	Pull chain with end bell	On-off	Nickel	<input type="checkbox"/> 442
3	250					
6	125					
3	250	Two-circuit	Pull chain with end bell	Lo-med-hi-off	Brass	<input type="checkbox"/> 460*
6	125					

\*cULus Listed

## Circuit control/toggle switch

### Product description

Single-pole  
 3A, 250V/AC  
 6A, 125V/AC

### Features

- Shank is threaded 15/32"-32 x 9/32" (7.1mm) long
- Keyed shank, indicator plate and finishing nut furnished
- 6" (152.4mm) wire leads, #18 105°C stripped 0.75" (19.1mm)


### Incandescent lampholders



Rating		Circuit	Description	Sequence	Catalog no.
A	V/AC				
3	250	SPST	Metal bat handle	On-off	<input type="checkbox"/> 452
6	125				

### Color information:

Nickel, brass



(Nickel)

(Brass)

Compliances, specifications and availability are subject to change without notice.