



Kick Space Heater

Low-profile fan-forced heater that provides comfort in places where space is limited (i.e. under-counter, stair riser etc.).



Features

- Single model offers flexible wattage output and voltage selection
- Makes an economical floor warmer
- Superior finned tubular element design
- Automatic primary and secondary reset thermal cutout for safety
- Pilot light will activate if unit trips on high limit

Applications

Kitchen | Bathroom |
Under-cabinet | Stair riser

Specifications

Voltage	- 120, 240/208V
Wattage	- Five outputs ranging from 450W to 1800W
Color	- Black or White
Airflow	- 80 CFM
Finish	- Polyester/epoxy powder coating resists fading and abrasion
Construction	- The enclosure is constructed of 20 gauge steel - Horizontal mount only
Heating Element	- The Kick Space heater has four totally enclosed nickel chromium resistance elements with steel sheaths - The elements are complete with spiral steel fins that are brazed to the steel sheath to provide excellent heat transfer
Control & Wiring	- The Kick Space heater is factory wired for 240/208V @ 900/675W and is field convertible for 240/208V @ 1800/1350W, 120V @ 450, 900, 1350, or 1800W configuration - The unit is controllable from a line voltage wall thermostat or field installed built-in tamperproof single or double pole thermostat kit
Warranty	- 1-year limited warranty on complete unit

Control Options (field installed)

Cat. No.	Description
CKHATD13	Single pole thermostat
CKHATD23	Double pole thermostat

Note: Adjust thermostat with pliers

Ordering Guide

Cat. No.	Watts	BTU	Volts	Weight (kg/lbs.)
CKHA20D31	450	1535	120	6.4 / 14
	900	3071	120	
	1350	4606	120	
	1800	6142	120	
	900 / 675	3071 / 2303	240 / 208	
	1800 / 1350	6142 / 4606	240 / 208	

Note: Standard color is Black – To order White add "W" at end of Cat. No. Factory wired at 240/208V for 900/675W

Dimensions

