


# nVent CADDY Slick Nut – SLICK375



- Provides fast universal attachment of threaded rod and hardware to standard strut profiles



Part Number	SLICK375
Material	Polyamide Spring Steel
Finish	nVent CADDY Armour
Hole Size (HS)	3/8"
Hole Type	Threaded
Height (H)	11/16"
Torque (TQ)	10 ft lb
Static Load 1 (F1)	600 lb
Static Load 2 (F2)	100 lb
Static Load 3 (F3)	250 lb
Standard Packaging Quantity	100 pc
UPC	78285641672

Indicated loads are independent of the threaded stud or rod.

Indicated loads are applicable on 14 GA and 12 GA (2 mm and 2.5 mm) strut channels only.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

