

Features

- Effectively support non-metallic sheathed and MC/AC cables
- Secures cables 1-1/4" from the face of the stud
- Flared edges prevent damage to the cable jacket
- Holds up to four MC/AC cables or four 12-3 non-metallic sheathed cables with ground
- Unique "stop-bend" design helps prevent cables from being installed too far from face of stud
- Patent pending design
- cULus® Listed

Non-Metallic Sheathed Cable and MC/AC Cable Support

CER4



Every installer knows how frustrating it can be when cables are pushed or pulled out of a location during the drywall phase. To resolve this situation, ERICO® has developed an innovative cable support to maintain the 1-1/4" spacing from the face of the stud that is required by the NEC®.

Suitable for both non-metallic sheathed cables and MC/AC cables, the CER4, part of the CADDY® line of fasteners, is the next generation of the popular CJ6 cable support.

The CER4 has a variety of unique features, including flared edges to prevent damage to the cable jacket and a "stop-bend" design, which keeps the cables centered and accounts for overcompensation by preventing them from being pushed too far from the face of the stud.

The CER4 is cULus® Listed and can support up to four cables at once.

Note: When supporting non-metallic sheathed cable in Canada, the CER4 can only be used on wood studs.



Metal Stud with Non-metallic sheathed cable



Metal Stud with MC/AC Cable

Part Number	Description	Standard Packaging Quantity
CER4	Non-Metallic Sheathed and MC/AC Cable Support	100

Cable Capacity					
Cable Size	MC/AC				ROMEX®
	14-2 w. ground	12-3 w. ground	12-4 through 10-4	single cables up to 6-3 stranded	up to 12-3 w. ground
No. of cables	4	3	2	1	4

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

cULus is a registered trademark of Underwriters Laboratories, Inc. NEC® is a registered trademark of, and National Electrical Code (NEC®) standard is a copyright of the National Fire Protection Association.

Copyright ©2009 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

Phone: 800-853-0878

Fax: 800-462-4797

www.erico.com

