

Split Ring Hangers



Split Ring Hangers

CADDY SUPERFIX 454 Standard Duty

- Recommended for the suspension of stationary non-insulated pipe lines
- Easy-to-close clamp for steel pipe and copper tube
- Unique hinged design eliminates the need to disassemble the clamp prior to installation
- Clamp can be closed with one hand, without ever turning a screw
- All-steel design of the closing mechanism retains strength even when exposed to heat
- Conforms with Manufacturers Standardization Society (MSS) SP-58 (Type 12)
- Comes with a welded 3/8" cap nut, allowing easy attachment to threaded rod



Material: Steel, EPDM-SBR Rubber

Finish: Electrogalvanized

Temperature: -58 to 230 °F

Part Number	Description	F ↓
454001	0.472"–0.551" OD, 1/4" Pipe, 3/8" Copper Tube	180 lb
454002	0.591"–0.748" OD, 3/8" Pipe, 1/2" Copper Tube	180 lb
454003	0.75"–0.828" OD, 5/8" Copper Tube	180 lb
454004	0.827"–0.906" OD, 1/2" Pipe, 3/4" Copper Tube	180 lb
454005	1.024"–1.102" OD, 3/4" Pipe, 1" Copper Tube	180 lb
454006	1.26"–1.378" OD, 1" Pipe, 1 1/4" Copper Tube	180 lb
454007	1.575"–1.693" OD, 1 1/4" Pipe, 1 1/2" Copper Tube	180 lb
454008	1.89"–2.047" OD, 1 1/2" Pipe	180 lb
454009	2.125"–2.283" OD, 2" Copper Tube	180 lb
454010	2.244"–2.402" OD, 2" Pipe	180 lb
454011	2.48"–2.638" OD, 2 1/2" Copper Tube	300 lb
454012	2.744"–2.874" OD, 2 1/2" Pipe	300 lb
454013	2.906"–3.156" OD, 3" Copper Tube	300 lb
454014	3.268"–3.583" OD, 3" Pipe	300 lb
454015	3.625"–3.937" OD, 3 1/2" Copper Tube	300 lb
454016	3.976"–4.173" OD, 3 1/2" Pipe, 4" Copper Tube	300 lb
454017	4.252"–4.488" OD, 4" Pipe	300 lb