CADDY® PYRAMID ST Fixed Strut Supports













- Strut-based thermoplastic support designed specifically for rooftop applications
- Provides superior support for pipe, conduit, duct, cable tray and equipment
- Solid bottom surface protects the roof membrane from damage caused by concentrated pressure
- Offers excellent load distribution with high load ratings
- Base is manufactured from UV-stabilized thermoplastic material
- Engineered for long-lasting performance
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credit





Material: Steel, Polypropylene Finish: Hot-dip galvanized Temperature: -30 – 130 °F Static Load Safety Factor: 3:1

Part Number	Height H	Length 1 L1	Length 2 L2	Width W	Surface Area	Weight	Static Load F
RPS360400	4.8"	10"	12 1/2"	8"	95 in²	3 lb	1,000 lb
RPS360401	6.4"	10"	12 1/2"	8"	95 in²	5 lb	1,000 lb
RPS360403	4.8"	16"	18 1/2"	8"	141 in²	5 lb	1,500 lb
RPS360404	6.4"	16"	18 1/2"	8"	141 in²	7 lb	1,500 lb

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.

