


Specification grade GFCIs

Specification grade tamper resistant ground fault circuit interrupter receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC; 20A, 125V/AC,
NEMA 5-15, 5-20



5-15R 5-20R



TRSGF15_MOD



WRSGF15



TRSGFNL15

Tamper resistant specification grade GFCIs



Rating		NEMA	Description	Color suffix	Catalog no.	▶▶	USA
A	V/AC						
15	125	5-15R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, V, W	□ TRSGF15__	•	
			Duplex GFCI, mid-size wallplate, back & side wire	A, LA, V, W	□ TRSGF15__-M		
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ TRSGF15F__	•	•
			Duplex GFCI with nightlight, back & side wire	A, BK, LA, V, W	□ TRSGFNL15__	•	
20	125	5-20R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, RD, V, W	□ TRSGF20__	•	
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ TRSGF20F__	•	•
			Duplex GFCI with nightlight, back & side wire	A, BK, LA, V, W	□ TRSGFNL20__	•	

Weather resistant specification grade GFCIs



Rating		NEMA	Description	Color suffix	Catalog no.	▶▶	USA
A	V/AC						
15	125	5-15R	Duplex GFCI, back & side wire	B, GY, V, W	□ WRSGF15__	•	
			Duplex GFCI, back & side wire	B, GY, V, W	□ WRSGF15F__	•	•
20	125	5-20R	Duplex GFCI, back & side wire	B, BK, GY, V, W	□ WRSGF20__	•	
			Duplex GFCI, back & side wire	B, GY, V, W	□ WRSGF20F__	•	•

Tamper & weather resistant specification grade GFCIs



Rating		NEMA	Description	Color suffix	Catalog no.	▶▶	USA
A	V/AC						
15	125	5-15R	Duplex GFCI, back & side wire	B, GY, LA, V, W	□ TWRSGF15__	•	
			Duplex GFCI, back & side wire	B, GY, LA, V, W	□ TWRSGF15F__	•	•
20	125	5-20R	Duplex GFCI, back & side wire	B, GY, LA, V, W	□ TWRSGF20__	•	
			Duplex GFCI, back & side wire	B, GY, LA, V, W	□ TWRSGF20F__	•	•

Includes standard size unbreakable wallplate unless otherwise noted
Consult factory customer service representative for additional packaging options

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

A	B	BK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

▶▶ ArrowLink option available. Add "MOD" suffix to standard catalog number (example VGF15W, VGF15WMOD). For ordering information on ArrowLink & ArrowLink SPD connectors

USA Indicates NAFTA compliant



Tamper resistant



Weather resistant



Tamper & weather resistant

Specification information: Pages 9 & 10

Compliances, specifications and availability are subject to change without notice.