

THREADERS

MODEL 700 HAND-HELD POWER DRIVE



Model 700



Model 600-I



Model 690-I



	MODEL 700	MODEL 600-I	MODEL 690-I
Pipe Capacity	½"–2" (3 mm–50 mm)	½"–1¼" (3 mm–32 mm)	½"–2" (3 mm–50 mm)
Bolt Capacity	¼"–1" (6 mm–25mm)	N/A	N/A
Weight (power drive only)	25 lbs. (11 kg)	12.7 lbs. (5.8 kg)	21.1 lbs. (9.59 kg)
Length	28¼" (71.7 cm)	20" (508 mm)	24" (613 mm)
Operating Speed (no load)	26–30 RPM	36 RPM	36 RPM
Die Heads	12-R or 11-R/00-R/00-RB*	11-R	11-R
Dies	12-R	12-R	12-R
Usage/Applications	Heavy-Duty/Mech/ Elect Contractor/ Maintenance	Service/ Repair Plumber (1¼")	Service/ Repair Plumber/ Maintenance (2")
Certifications/Approvals	UL/CSA/RoHS/WEEE	UL/CSA/RoHS/WEEE	UL/CSA/RoHS/WEEE

*With adapter

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT	
			LB.	KG
41935	700	115V 50/60 Hz Only	25	11
45178	700	700 Power Drive w/ ½"–2" NPT Die Heads, Case and Support Arm	–	–
44913	600-I	115V w/o Die Heads w/Case Only and Support Arm	29.1	13.2
44918	600-I	115V ½"–2" NPT w/Case and Support Arm	41	18.6
44928	690-I	115V w/o Die Heads w/Case Only and Support Arm	40	19.2
44923	690-I	115V ½"–2" NPT w/Case and Support Arm	59.4	26.9

RIDGID Die Head Quick Release System (690-I only)



TURN TO UNLOCK



PULL DIE HEAD



RELEASE TO LOCK