GASTITE® – THE FLEXIBLE ALTERNATIVE

PRODUCT DESCRIPTION:

Gastite[®] is CSA design certified to ANSI LC1-2005 for "Fuel Gas Piping Systems Using Corrugated Stainless Steel Tubing (CSST)." CSST supplies natural gas or liquefied petroleum gas (LP gas) to appliances. Simple hand tools such as tubing cutters, wrenches and utility knives are all that are needed to work with the Gastite[®] components. Gastite[®] is a reliable, cost-effective system that can be installed in all modes of construction: residential, commercial and industrial; new construction and retrofits.

Featuring its patent-pending multi-point seal, the XR2 fitting's sealing surface does not sit on the cut end of the tubing, so even the most unsightly cut will yield a tight seal. The XR2 fitting is also reduced in size and requires minimal torque, making the installation of larger sizes considerably easier. With no orings or gaskets, the reusable brass components provide a reliable metal-to-metal installation.

CUSTOMER SERVICE AND TECHNICAL SUPPORT ARE ONLY A PHONE CALL AWAY AT 1-800-662-0208.

CODES & SPECIFICATIONS:

Recognized as a fuel gas piping material since 1988, Gastite[®] complies with ANSI LC1-2005 for "Fuel Gas Piping Systems Using Corrugated Stainless Steel Tubing (CSST)." The Gastite[®] system is listed by several independent third party laboratories and is recognized by model building codes throughout North America.

FEATURES & BENEFITS:

AIBLE GAS PIPING

LEXIBLE GAS PIPING

- Flexibility means quick and easy installations. Gastite[®] installs 30-70% faster than traditional piping methods.
- Pre-marked by the foot, there's no measuring, rigid pipe cutting or threading. This means less waste and fewer fittings.
- 75% fewer fittings in the average installation means a safer system, less leak potential and reduced callbacks.
- Gastite[®] CSST is lightweight 250 feet of 1/2" CSST weighs approximately 38 pounds and can be easily transported and handled on the job.
- Custom lengths of tubing and job-specific accessories for those large and multi-family projects can be easily obtained by a simple telephone call.





CORRUGATED STAINLESS STEEL TUBING (CSST):

APPLICATION:

• CSST flexible gas piping supplies natural gas or liquefied petroleum gas to appliances.

MATERIAL / SPECIFICATIONS:

- Tubing: ASTM A240 Type 304 Stainless Steel.
- Jacket: UV resistant Polyethylene complying with requirements of ASTM E84 25/50 Index for Flame and Smoke.

FEATURES AND BENEFITS:

- Flexibility and durability allows for simple routing through complex building structures and designs.
- Pre-marked by the foot for easy measuring and installation.
- Minimum tubing wall thickness of .010 on all sizes is more robust than other brands of CSST.
- Annealed 304 stainless steel makes tubing more flexible than brands not heat-treated.



CORRUGATED STAINLESS STEEL TUBING (CSST)

Part No.	Description	Pkg. Qty.	Lbs.	Reel Size (Dia. X Width)
S93-6A4-250	3/8" Corrugated Stainless Steel Tubing	250 Ft/Coil	28.0	20" x 12-1/2"
S93-6A4-50*		50 Ft/Box	4.3	21" x 6"
S93-6A4-125		125 Ft/Coil	17.5	20" x 12-1/2"
S93-6A4-500		500 Ft/Coil	50.0	20" x 12-1/2"
S93-6A4-1000		1,000 Ft/Coil	94.0	20" x 21"
S93-8A4-250	1/2" Corrugated Stainless Steel Tubing	250 Ft/Coil	38.0	20" x 12-1/2"
S93-8A4-50*		50 Ft/Box	6.2	21" X 6"
S93-8A4-125		125 Ft/Coil	22.2	20" X 12-1/2"
S93-8A4-500		500 Ft/Coil	69.0	21" x 21"
S93-8A4-1000		1,000 Ft/Coil	140.0	32" x 21-1/2"
\$93-8A4-1500		1,500 Ft/Coil	200.0	32" x 21-1/2"
893-11B4-250	3/4" Corrugated Stainless Steel Tubing	250 Ft/Coil	47.7	20" x 21"
S93-11B4-50*	o,g	50 Ft/Box	7.7	21" x 6"
S93-11B4-125		125 Ft/Coil	26.0	20" x 12-1/2"
S93-11B4-500		500 Ft/Coil	87.1	24" x 25"
S93-11B4-1000		1,000 Ft/Coil	170.4	32" x 21-1/2"
			(
\$93-16A4-150	1" Corrugated Stainless Steel Tubing	150 Ft/Coil	42.3	20" x 21"
S93-16A4-50		50 Ft/Coil	18.1	21" x 6"
S93-16A4-75		75 Ft/Coil	23.8	20" x 12-1/2"
S93-16A4-300		300 Ft/Coil	78.4	24" x 25" 22" x 21 1/2"
\$93-16A4-500		500 Ft/Coil	130.8	32" x 21-1/2"
893-20A4-150	1-1/4" Corrugated Stainless Steel Tubing	150 Ft/Coil	60.0	24" x 25"
S93-20A4-50		50 Ft/Coil	22.1	21" x 6"
S93-20A4-75		75 Ft/Coil	30.0	20" x 21"
\$93-20A4-300		300 Ft/Coil	103.8	32" x 21-1/2"
S93-24A4-150	1-1/2" Corrugated Stainless Steel Tubing	150 Ft/Coil	76.6	24" x 25"
S93-24A4-50	11/2 Corragated Statifiess Steer Fubling	50 Ft/Coil	29.4	20"x12-1/2"
S93-24A4-75		75 Ft/Coil	35.5	20" x 21"
S93-24A4-300		300 Ft/Coil	125.7	32" x 21-1/2"
S93-32A4-150	2" Corrugated Stainless Steel Tubing	150 Ft/Coil	108.0	32" x 21-1/2"
S93-32A4-150	2 Corrugated Statilless Steel Fubling	50 Ft/Coil	39.5	52" x 21-1/2 " 20"x12-1/2"
S93-32A4-50 S93-32A4-75		75 Ft/Coil	59.5 51.6	20"x12-1/2" 24" x 25"
S93-32A4-75		300 Ft/Coil	194.0	40" x 27-1/2"
37 3-32A+-3 00		500 Pt/ COII	174.0	TU A 2/-1/2

*Packaged in box. Please contact Gastite Customer Service for custom lengths.

