



FlashShield Termination Fitting with Flange, FSTRM-XX



Gastite Division
1116 Vaughn Parkway
Portland, TN 37148
Telephone 800-662-0208
www.gastite.com

Description

FlashShield™ is metallically shielded corrugated stainless steel tubing system complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICC and IAPMO. The FlashShield system is also listed to protective jacket standards, ICC-ES PMG LC1024, and LC1027. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing and Jacket-Bite™ jacket capturing for steel tubing protection and continuous conductivity.

Features:

- Male NPT Adapter, Bushing, Termination Nut, Corrosion Resistant Steel Flange
- For "Fixed-Point" Termination on Floor or Wall
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Self-Guiding Fitting Assembly
- Patented Jacket Bite™
- Fully Reusable Fitting




Listings:

- CSA Certificate 2728525
- ICC-ES Report No. PMG 1066 and PMG 1155
- IAPMO: File No. C-3250 and Report No. 0239

Technical Data:

Max. Approved Operating Pressure	25 psi
Operating Temperature Range	-40°F to 160°F
Fitting Material	CA360



Dimensional Characteristics

Size	P/N	Assembled Length	Pipe Thread	Flange Thread	Nut Hex	Fitting Hex	Flange O.D.	Mounting Hole Pattern (dia.)	Assembly Torque (ft-lbs)
1/2"	FSTRM-8	2.541"	1/2"	3/4"	1-1/4"	1-1/8"	2-5/8"	2-3/4"	35
3/4"	FSTRM-11	2.691"	3/4"	1"	1-9/16"	1-3/8"	2-5/8"	2-3/4"	45
1"	FSTRM-16	2.748"	1"	1-1/4"	1-15/16"	1-3/4"	2-5/8"	2-3/4"	65
1-1/4"	FSTRM-20	3.056"	1-1/4"	1-1/2"	2-3/16"	2-1/16"	3-1/4"	3-1/4"	95

FlashShield fittings can be used with Gastite and FlashShield CSST.