



Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Frame-In Kit	Reflector Trims — See Individual Reflector Trim Specification Sheets									
	Open Downlight						Adjustable		Enclosed Diffusers	Wall Washer
	Alzak®	Satin Cone	Sloped Ceiling	Baffles	Basic White	Cross Blade	Recessed Line Volt.	Recessed Low Volt.		
1100IC	Reflector: 1143 1144	1108 1110	1131 1131WH 1131GD 1131CL 1131BK	1105 1105WH 1175 1176 1176WH	1170M1 1171	1132	1129 1129WH 1129CL 1129GD 1129BK	1155 1155WH 1158 1160 1161	1121 1124 1126 1128 1134	1185 1186 1186WH
1100ICM 3/8" Integral Plaster Lip	Cone: 1112 1113 1113BK 1113WH		1133 1133WH 1133GD 1133CL 1133BK	1179M1 1179WH			Eyeball: 1122 1122WH 1123 1123WH 1182	1161WH 1163 1164	1177SH 1178SH	

Features

- Housing:** 0.026" (#20 ga.) galvanized steel. U.L. listed for direct contact with thermal insulation. Access door for inspection of junction box.
- Mounting Frame:** 0.036" (#20 ga.) galvanized steel. Accommodates all ceilings up to 1" thick. ICM version has 3/8" deep integral lip. Four slots are positioned 90° apart to simplify alignment. Push-in/twist-out rotoclips hold reflector flush to ceiling.
- Junction Box:** 2" x 4" x 4", 0.063" (#14 ga.) galvanized steel. U.L. listed for maximum of 6 No. 12 ga., 90°C through branch circuit conductors. Quick release "L" shaped cover for outside access to wiring. Access door inside of housing allows easy inspection of wiring without removal of housing. Integral cable clamps permit attachment of nonmetallic Romex® or armored cable without the need for additional connectors.
- Mounting Bars:** 0.059" (#16 ga.) galvanized steel. 13" long bars extend to 27", rotatable and lockable, with integral T-bar tabs. Attach to wood joist or T-bar ceilings without need of accessories.
- Socket Housing:** Impact extruded aluminum or galvanized steel.
- Socket:** Porcelain medium base; nickel plated screw shell. Pre-wired with #18 ga. SF1 leads to junction box.
- Thermal Protector:** Meets NEC and U.L. requirements. Located inside housing.

Options & Accessories

- Mounting Bars:** **1976** - 13" set of (4)
Concealed Spline Ceiling Kit: **1965** - set of (4), 1 1/2" to 2 1/2" Mtg. Ht.
Plaster Ceiling Ring: **1961** - 7/8" depth for wet plaster ceilings. Not for use with ICM housing.
Extra-Thick Ceiling Mounting Ring: **1967A** - up to 2" thick ceilings.

Labels

UL (Type I.C., Suitable for Damp Locations), I.B.E.W.

Romex® is a registered trademark of General Cable Industries Inc.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • B0902