

Rockslide Preset Slide Dimmers



Rockslide Preset*
600W, 1000W



Rockslide
Preset* Remote

ROCKSLIDE PRESET SLIDE DIMMERS

Incandescent

DESCRIPTION	ITEM NUMBER	COLOR SUFFIX	WATTAGE CAPACITY	WIRING DIAG. PP. 32-33	NOTES PP. 34-35
Incandescent	RS600	-W -I	600W	A	1, 1S
	RS1000	-W -I	1000W	A	1, 1S

Inductive
(Neutral connection required)

Inductive (Neutral connection required)	RS600VA	-W -I	600VA	B	1, 1S
	RS1000VA	-W -I	1000VA	B	1, 1S

ROCKSLIDE PRESET REMOTE

Multi-location/3-way

Multi-location/3-way	RS3R	-W -I	n/a	I	8A
----------------------	------	-------	-----	---	----



Astral™ Slide Dimmers



Astral Non-Preset*
600W



Astral Preset*
600W

DESCRIPTION

ASTRAL NON- PRESET SLIDE DIMMERS

Incandescent

DESCRIPTION	ITEM NUMBER	COLOR SUFFIX	WATTAGE CAPACITY	WIRING DIAG. PP. 32-33	NOTES PP. 34-35
Incandescent	A600	-WC-IC	600W	A	1, 1S

Magnetic Low-Voltage, 2-Wire
(No neutral connection required)

Magnetic Low-Voltage, 2-Wire (No neutral connection required)	A600LV	-WC-IC	600VA	A	1, 1S
--	--------	--------	-------	---	-------

ASTRAL PRESET DIMMERS

Incandescent

Incandescent	AP600	-WC-IC	600W	A	1, 1S
	AP603 (3-way)	-WC-IC	600W	C	1, 1S, 9A

Magnetic Low-Voltage

Magnetic Low-Voltage	AP600LV	-WC-IC	600VA	A	1, 1S
	AP603LV (3-way)	-WC-IC	600VA	C	1, 1S, 9A

WHISPURR PRESET FAN CONTROL

WHISPURR PRESET FAN CONTROL	APWHIS	-WC-IC	1.5 Amp/3-speed	N	1, 1S, 10E
-----------------------------	--------	--------	-----------------	---	------------

All 600W strap dimmers can be installed into a multi-gang configuration to fully rated load without derating. See page 34, note 1C for load calculations.

Features:

- Full-range dimming
- Multi-location/3-way control

Rockslide

- Red LED night light
- Matches decorator-style switches
- Clean mini slider


Astral

- Captive knob
- Easy on/off preset


Dimensions:

	Width (W)	Height (H)	Depth (D)
Rockslide Strap	= 1.68"	4.00"	1.37"
Astral Strap	= 1.67"	4.06"	1.32"

Rockslide



Astral



Available in Clamshell Packaging (White=WC, Ivory=IC)

* Shown with Compli® Designer Faceplates, sold separately. See pages 28-29. Also fits designer style faceplates by others.

Dimmer must be located at the load side when used in a 3-way installation

Color Code	
White	Ivory
W	I