

Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Reflector Trim	Frame-In Kit — See Individual Frame-In Kit Specification Sheets							
	LED				Fluorescent			
1177SH Lexan®	Frame-In Kit	Installation Type	Lamping	Height	Frame-In Kit	Installation Type	Lamping	Height
	1101LED	Non-IC	LED	7 1/2"	1101F18U Series	UniFrame™ Non-IC	(1) Quad/Triple 18W (GX24q-2)	6 5/8"
	1100LEDREM	Non-IC Remodeler	LED	7 1/2"	1101F2642U Series	UniFrame™ Non-IC	(1) Triple 26/32W (GX24q-3)	6 5/8"
	L56LED	Non-IC Retrofit	LED	7 1/2"				
	Incandescent							
	1102P1	Non-IC	60W A19	7 1/2"	1104F18 Series	IC	(1) Quad/Triple 18W (GX24q-2)	7 1/2"
	1103R	Non-IC Remodeler	60W A19	7 1/2"	1104F26 Series	IC	(1) Quad/Triple 26W (GX24q-3)	7 1/2"
	1100IC	IC	40W A19	7 5/16"	1100FTU Series	Non-IC	(1) Triple 26/32W (GX24q-3)	7 5/8"
	1100AICM	AirSeal® IC	40W A19	7 5/16"				
	1100DICM	Deep IC	40W A19	9 1/4"				
	1100DAICM	Deep AirSeal® IC	40W A19	9 1/4"	1101FDICMX1/N	Performance IC Advance Mark10 Dimming 120v	(1) Triple 26/32W (GX24q-3)	7 1/4"
	1104IC/N	Non-IC	40W A19	7 1/2"	1101FDICMX2/N	Performance IC Advance Mark10 Dimming 277v	(1) Triple 26/32W (GX24q-3)	7 1/4"
	1104ICR	Non-IC Remodeler	40W A19	7 1/2"	1910XDH1	Conversion Kit	(2) Quad 13W (GX23-2)	7 5/8"

Features

- Reflector:** Hydroformed aluminum, .040" minimum thickness (18 ga.); Anobrite® (anodic-processed) semi-specular finish for permanent reflectivity; plastic white trim flange.
- Flush Diffuser:** Translucent white, break resistant polycarbonate Lexan®. Installs and removes with twist-lock actions; no tools required.
- Frame-In Kit:** (1102P1 standard frame shown). Other frames listed above and shown on the right. See Frame-In Kit specification sheets for more details.


Labels

UL (Suitable for Wet Locations - Covered Ceiling), I.B.E.W.
Meets NEC® requirements for Spas and Hot Tubs.

NEC® is a registered trademark of the National Fire Protection Agency.


Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2011 Genlyte Group LLC • I0911



Use quick calculator chart to determine the spacing of 2 Lt. Watt Quad Tube units for a desired level of illumination. Conversion Factors: 1 Lt. 13W Quad Tube, F.C. x 0.5. 60W A19, F.C. x 1.0.

SPACING RATIO = 1.2



COEFFICIENTS OF UTILIZATION
% EFFECTIVE CEILING CAVITY REFLECTANCE

ROOM CAVITY RATIO	% EFFECTIVE CEILING CAVITY REFLECTANCE															
	80			70			50			30			10			0
	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
1	.16	.16	.15	.16	.16	.15	.15	.15	.15	.15	.14	.14	.14	.14	.13	
2	.15	.14	.13	.14	.13	.13	.14	.13	.12	.13	.13	.12	.13	.12	.11	
3	.13	.12	.11	.13	.12	.11	.12	.11	.10	.12	.11	.10	.11	.11	.10	
4	.12	.10	.09	.11	.10	.09	.11	.10	.09	.11	.10	.09	.10	.09	.09	
5	.10	.09	.08	.10	.09	.08	.10	.09	.08	.09	.09	.08	.09	.08	.07	
6	.09	.08	.07	.09	.08	.07	.09	.08	.07	.09	.08	.07	.08	.07	.06	
7	.08	.07	.06	.08	.07	.06	.08	.07	.06	.08	.07	.06	.07	.06	.06	
8	.07	.06	.05	.07	.06	.05	.07	.06	.05	.07	.06	.05	.07	.06	.05	
9	.07	.06	.05	.07	.05	.05	.07	.05	.05	.06	.05	.05	.06	.05	.04	
10	.06	.05	.04	.06	.05	.04	.06	.05	.04	.06	.05	.04	.06	.05	.04	

20% FLOOR CAVITY REFLECTANCE

Conversion Factors: 1 Lt. 13W Quad Tube, C.U. x 1.0. 60W A19, C.U. x 2.0.

To convert lighting data for a lower wattage incandescent lamp of the same type, multiply the footcandle (or candlepower) values by the ratio of the lumens of the two lamps. The coefficients of utilization remain the same.

Job Information **Type:**

Lightolier a Genlyte company www.lightolier.com
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2011 Genlyte Group LLC • I0911

LIGHTOLIER