

About the Lytening series

5 1/2" thru 7" frame-in kits

Units featuring reflectorized lamps, such as PAR and BR lamps, are a good choice for accent lighting and wall washing, or wherever highly controlled beams are desired. Small-scale halogen PAR lamps such as the PAR16, PAR20, and PAR30 produce crisp, white light that is very similar in effect to low voltage lighting. Lytecaster downlights designed around these light sources are an excellent way to achieve the look and feel of low voltage accent lighting without the cost or complexity of transformers.



Lytening convertible remodeler IC/non-IC

Remodeler may be used in existing insulated or non-insulated ceilings up to 2" thick. Junction box on flex for easier mounting in restricted applications. AirSeal® ready, complies with MEC and WSEC air leakage requirements when installed as instructed. Integral cable clamps for nonmetallic (Romex®) cable.



	1004ICR	1104ICR
Cut out (A)	5 3/8"	7"
Width (W)	5 3/4"	7 5/16"
Length (L)	11 3/8"	13 1/8"
Depth* (D)	7 1/2"	7 1/2"

Lytening shallow convertible IC/non-IC

Shallow remodeler IC/Non-IC housing for use in 2" x 6" joist construction. Junction box on flex for restricted applications. AirSeal® ready, complies with MEC and WSEC air leakage requirements when installed as instructed.



	1004SICR	1104SICR
Cut out (A)	5 1/2"	6 13/16"
Width (W)	5 3/4"	7 5/16"
Length (L)	11 3/8"	13 1/8"
Depth* (D)	5 1/2"	5 1/2"

Lytening shallow convertible IC/non-IC

Shallow new construction IC/Non-IC housing for use in 2" x 6" joist construction. Pivoting bar-ends, tool-free cable clamps for nonmetallic (Romex®) cable and pre-installed mounting screws are standard. AirSeal, complies with MEC and WSEC air leakage requirements when installed as instructed. UL listed for through wiring, mounting bars lock to T-bar ceiling runners without accessories.



1104SICN
Preset Nails

1004SICN
Preset Nails

	1004SIC	1104SIC
Cut out (A)	5 3/8"	6 13/16"
Width (W)	5 3/4"	7 5/16"
Length (L)	9"	10 3/4"
Depth* (D)	5 1/2"	5 1/2"

Lytening IC

IC housing designed to offer a full range of lighting performance in fully insulated ceiling applications up to 1" thick. Accepts a wide choice of reflector trims and lamps to 120W. AirSeal® complies with MEC and WSEC air leakage requirements. Pivoting bar-ends, pre-installed mounting screws (or nails), and tool-free cable clamps for fast, convenient installation.



1104ICXQ
Quick connects

1004ICXQ
Quick connects

1104ICXN
Preset nails

1004ICXN
Preset nails

1104ICXNQ
Preset nails / quick connects

1004ICXNQ
Preset nails / quick connects

	1004ICX	1104ICX
Cut out (A)	5 1/4"	6 15/16"
Width (W)	10 3/8"	10 3/8"
Length (L)	12 1/4"	12 1/4"
Depth* (D)	7 1/4"	7 1/4"

Lytening convertible IC/non-IC

Convertible IC/Non-IC for new construction ceilings up to 3" thick. AirSeal®, complies with MEC and WSEC air leakage requirements when installed as instructed. Pivoting bar-ends, pre-installed mounting screws, and tool-free cable clamps for fast, convenient installation. Mounting bars lock to T-bar ceiling runners without accessories, UL listed for through wiring.



1104ICQ
Quick connects

1004ICQ
Quick connects

1104ICN
Preset nails

1004ICN
Preset nails

1104ICNQ
Preset nails / quick connects

1004ICNQ
Preset nails / quick connects

	1004IC	1104IC
Cut out (A)	5 3/8"	7"
Width (W)	5 3/4"	7 5/16"
Length (L)	9"	10 3/4"
Depth* (D)	7 1/2"	7 1/2"