# Closet Auger

# Three Foot Flexicore®

Professional 3 ft. Flexicore<sup>®</sup> Closet Auger is the ideal tool for breaking up stoppages or removing lost objects in clogged toilet bowls. Durable double layer Flexicore construction gives the snake tremendous resistance to kinking. The Flexicore closet auger works where plungers fail.

The tough outer steel tube is 3/4" in diameter. Inside, a galvanized steel rod turns the cable. Other features include a vinyl bowl guard, vinyl grip handle and turning handle, and a "Grip Clip" for securing the cable.

Catalog Number		Weight/Pounds
3FL	Regular Head	4-1/2
3FL-DH	Down Head	4-1/2

## Six Foot Teletube®

Heavy-duty 6 ft. Teletube<sup>®</sup> Closet Auger clears stoppages beyond the bowl. No need to lift the bowl, because the Teletube has an extra three feet telescoped inside a guide tube until you need it. After you've worked the first three feet into the bowl, you can go three feet farther simply by pressing a button and pulling the crank handle.

Outer steel tube is a big 1-1/8" in diameter. The hexagonal guide tube is even tougher than the steel rod we use in our 3FL closet augers. The Teletube weighs just a little more than a 3FL too. Other features include a vinyl bowl guard, vinyl grip handle and turning handle, and a "Grip Clip" for securing the cable.

Catalog Number		Weight/Pounds
T6FL	Regular Head	5-3/4
T6FL-DH	Down Head	5-3/4

3/4" O.D. Brass Finish Steel Tube

3FI

15/32" O.D. Double Layer Flexicore Construction Grip Clip -

> 3/8" Galvanized Steel Rod ———

T6FL-DH

Vinyl Guard Protects Bowl

> 1-1/8" O.D. Brass Finish Steel Tube

Vinyl Grip Handle with Grip Clip



#### Closet Auger Bag Closet Auger Bag keeps the closet auger contained and out of sight as it's carried to

closet auger contained and out of sight as it's carried to and from the job.



### Down Head

Flexible down head follows bowl contours. It springs through sharply angled passages while protecting the inner walls from chipping and breaking.



## Flexicore® Cable

**Double Spring Construction** 

Two layers of tempered spring steel are coiled tightly over a core of 49-stand wire rope. It gives the tool tremendous resistance to kinking. So tough it carries a one-year warranty against defect or breakage Flexicore Patent Nos. 2,244,735 and 2,849,870

> Hexagonal Guide Tube

Press button, pull back on handle, and you've released three more feet of cable.

Cutaway