



UNDERGROUND UF SPLICE KIT

Accommodates waterproof splicing of #14 - #8 AWG UF copper wire.

- Connector set screws engage each wire securely for a solid splice.
- Minimum conductor size 14/2 with ground.
- Maximum conductor size 8/3 with ground.
- 600 V rating.




Part #	Pkg Qty	Description
HST-1300	1 kit	Complete waterproof installation for UF cables



Kit Contains:

Qty	Description
4	Screw Splice Connectors
1	8" Heavy Wall Polyolefin Heat Shrink Tubing with Watertight Adhesive Liner



BUTT SPLICE KIT

Used for waterproof installation or repair of #2 - #8 AWG copper cable.

- Easy to use.
- Seal with heat gun or torch.
- Eliminates messy epoxies, tapes, or mastics.
- Rated at 600 V maximum.




Part #	Pkg Qty	Description
HSB-28	1 kit	Cable Splice Kit



Kit Contains:

Qty	Description
1	Screw Splice Connector
1	4" Heavy Polyolefin Shrink Tube with Watertight Adhesive Liner



BUTT SPLICE CONNECTOR KIT

Used for waterproof repair of well pipe cables and splices of stranded cable #8 - #14 AWG.

- Connector set screws engage each wire securely for a solid splice.
- Assures safe and permanent connections.
- Rated at 600 V maximum.



Part #	Pkg Qty	Description
HST-WP	1 kit	Well Pipe Wire Splice Kit



Kit Contains:

Qty	Description
1	Screw Splice Connector
1	4" Heavy Polyolefin Shrink Tube with Watertight Adhesive Liner