

WIRE CONNECTORS




WIREGARD™ COLOR-CODED SCREW-ON WIRE CONNECTORS

The industry's standard twist-on connector with quality performance and durability.

- Color-coded for easy size selection.
- Tight, square-wire spring makes quick, secure connections for positive continuity.
- Tough, thermoplastic shell shields against environmental extremes.
- Resists chemical action from hydrocarbons, dilute acid or alkaline solutions.
- Flame-retardant properties resist heat distortion up to 105 °C (221 °F).
- High-dielectric shell features deep skirt design to prevent exposure of bare wire.
- Copper to copper connections only.

WIRE CONNECTING, TERMINATION, & CONTROL



Dimensions

Model	A	B	C	D	E
GB-1	37/64	11/64	1/8	1/4	21/64
GB-2	45/64	11/64	3/16	5/16	25/64
GB-3	27/32	21/64	13/64	11/32	7/16
GB-4	15/16	17/64	15/64	7/16	35/64
GB-6	11/16	17/64	21/64	17/32	21/32

SEE PAGE 9
for info on Assortments & Kits

	Color	Part #	Pkg Qty	Wire Range	Min	Max
GB-1 / 71B		10-001	100/box	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
		11-001	1,000/bulk case	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
		12-001	25,000/bulk keg	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
		16-001	150/jar	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
		19-001	14/card	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
		25-001	25/resealable bag	#22 - #16 AWG ¹	1 #20 w/1 #22	2 #16
GB-2 / 72B		10-002	100/box	#22 - #16 AWG ¹	3 #22	3 #16
		11-002	1,000/bulk case	#22 - #16 AWG ¹	3 #22	3 #16
		12-002	10,000/bulk keg	#22 - #16 AWG ¹	3 #22	3 #16
		16-002	150/jar	#22 - #16 AWG ¹	3 #22	3 #16
		19-002	14/card	#22 - #16 AWG ¹	3 #22	3 #16
		25-002	25/resealable bag	#22 - #16 AWG ¹	3 #22	3 #16
GB-3 / 73B		10-003	100/box	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		11-003	1,000/bulk case	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		12-003	10,000/bulk keg	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		13-003	10,000/keg ⁴	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		16-003	100/jar	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		16-003L	700/jar	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		17-003	50/bag	#22 - #14 AWG ³	4 #20	5 #16 w/1 #20
		18-430	400/bag	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		19-003	12/card	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
		25-003	25/resealable bag	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20
50-003	6,000/bucket ⁶	#22 - #14 AWG ³	3 #20	4 #16 w/1 #20		
GB-4 / 74B		10-004	100/box	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		11-004	1,000/bulk case	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		12-004	10,000/bulk keg	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		13-004	10,000/keg ⁴	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		16-004	200/jar	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		16-004L	400/jar	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		17-004	50/bag	#18 - #10 AWG ³	2 #14 w/1 #18	5 #14
		18-440	400/bag	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		19-004	9/card	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
		25-004	25/resealable bag	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14
50-004	4,000/bucket ⁷	#18 - #10 AWG ³	1 #14 w/1 #18	4 #14		
GB-6 / 76B		10-006	100/box	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		11-006	1,000/bulk case	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		12-006	5,000/bulk keg	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		13-006	5,000/keg ⁵	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		16-006	125/jar	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		16-006L	300/jar	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		17-006	50/bag	#18 - #10 AWG ³	3 #14	3 #10 w/2 #12
		18-260	200/bag	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		19-006	6/card	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		25-006	25/resealable bag	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12
		50-006	2,500/bucket ¹¹	#18 - #10 AWG ³	2 #14	2 #10 w/2 #12

¹ Connections rated at 300 V Max. ² Connections rated at 600 V Max. ³ Connections rated at 300 V Max. and 600 V Max.
Note: Connection rated at 600 + V Max. for Building Wiring and rated at 1000 V Max. in lighting fixtures/luminaries and signs.
See carton for detailed wire combination ratings.

⁴ 20 bags of 500 ea. ⁵ 20 bags of 250 ea. ⁶ 12 bags of 500 ea. ⁷ 8 bags of 500 ea. ¹¹ 10 bags of 250 ea.