

GT-15 Non-Contact Low Voltage Detector



The answer to your low voltage needs.

The GT-15 non-contact low voltage detector is the newest addition to Greenlee's broad offering of electrical test and measurement products. The GT-15 non-contact low voltage detector is a great tool when working in electrical environments where the voltage ranges are from 12 volts AC to 90 volts AC. Examples of low voltage environments include sensing the presence of AC voltage in thermostats, industrial controls, door bells and irrigation systems. The GT-15 non-contact low voltage detector's bright LED and audible alarm indicate that voltage is present. The cushioning grip provides for hours of tireless use.

The GT-15 non-contact low voltage detector meets all the requirements of UL and has a safety rating of Category III, 300V AC. The Category III, 300V AC rating is more than sufficient for most low voltage applications. Like all Greenlee test and measurement products, the GT-15 has a Lifetime Limited Warranty.

PRODUCT FEATURES

- Use to **detect voltage in low voltage applications** ranging from 12-90 volts AC.
- Safe, non-contact voltage detection.
- Bright LED and audible alarm sound if voltage is present.
- On/Off switch for longer battery life.
- Convenient pen-size device easily fits into pockets or tool pouches

CONTENTS/ACCESSORIES

• (2) 1.5 V AAA batteries

SPECIFICATIONS

Voltage Detection: 12-90VAC
Frequency: 50-500 Hz
Measurement category: CAT III, 300V



ORDERING INFORMATION

 CAT NO.
 UPC NO.
 DESCRIPTION
 QTY

 GT-15
 09023
 DETECTOR, NON-CONTACT (12-90V)
 10

DISTRIBUTED BY:



USA: 800-435-0786 Fax: 800-451-2632 815-397-7070 Fax: 815-397-1865 Canada: 800-435-0786 Fax: 800-524-2853 International: +1-815-397-7070 Fax: +1-815-397-9247

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070 ©2005 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA Greenlee Textron Inc. is a subsidiary of Textron Inc.

www.greenlee.com MA-4753