B = BARE TOOL

HOLE DIA.

HEX SHANK

WEIGHT

Nail Eater® Extreme



- Improved cutting edge provides 30% longer life span
- · Patented new design for improved cutting and cleaner holes
- · Self-feeding screw point draws bit through wood
- Patent Pending, cutting angle design smoother starts, reduced cutting loads
- Made of super tough, heat-treated steel; cuts through nails and provides longer life
- "Shorty" bits for working in tight places, yet still can go ٠ through three abutting 2x4s
- See "Bit Extensions" if more length is required (see page 205).
- P.O.P packaged

SPECIFICATIONS

Overall Length

Twist Lenath

NAIL EATER® EXTREME SHORTY

| Overall Length | 7-5/8" (193.7 mm) | | | | | |
|---------------------------|--|--|--|--|--|--|
| Twist Length | 5" (127 mm) | | | | | |
| Electrical drill required | 61 PTS – 5/8 through 61 PTS - 1, minimum 3/8" drill; All Big Shank, 1/2" drill. | | | | | |
| NAIL EATER® EXTREME | | | | | | |

18" (457.2 mm

15" (381 mm)

Nail Eater® Extreme Impact Bits

37868

FAX 800.524.2853

| CAT. NO. | UPC NO. | UPC NO. | INCH | MM | INCH | ММ | LBS | G |
|----------------|---------|---------|-------|------|------|------|-----|-----|
| 61PTS-5/8 | 30419 | — | 5/8 | 15.9 | 5/16 | 7.9 | .3 | 137 |
| 61PTS-3/4 | 30423 | _ | 3/4 | 19.1 | 5/16 | 7.9 | .4 | 182 |
| 61PTS-7/8 | 30427 | _ | 7/8 | 22.2 | 5/16 | 7.9 | .5 | 227 |
| 61PTS-1 | 30429 | — | 1 | 25.4 | 5/16 | 7.9 | .8 | 363 |
| 62PTS-5/8 | 31788 | _ | 5/8 | 15.9 | 7/16 | 11.1 | .3 | 137 |
| 62PTS-11/16 | 31790 | — | 11/16 | 17.5 | 7/16 | 11.1 | .4 | 182 |
| 62PTS3/4 | 31792 | 36640 | 3/4 | 19.1 | 7/16 | 11.1 | .5 | 227 |
| 62PTS-13/16 | 31794 | — | 13/16 | 20.6 | 7/16 | 11.1 | .5 | 227 |
| 62PTS7/8 | 31796 | 36642 | 7/8 | 22.2 | 7/16 | 11.1 | .6 | 273 |
| 62PTS-1 | 31798 | 36643 | 1 | 25.4 | 7/16 | 11.1 | .7 | 318 |
| 61/62PTS-1-1/8 | 30431 | _ | 1-1/8 | 28.6 | 7/16 | 11.1 | .9 | 409 |
| 61/62PTS-1-1/4 | 30433 | _ | 1-1/4 | 31.8 | 7/16 | 11.1 | 1.1 | 499 |

NAIL EATER® EXTREME

NAIL EATER® EXTREME SHORTY

POP

BULK

| | | POP | BULK | HOLE I | DIA. | HEX S | HANK | WEIG | HT |
|---|------------|---------|---------|--------|--|-------|------|------|------|
| | CAT. NO. | UPC NO. | UPC NO. | INCH | MM | INCH | ММ | LBS | G |
| | 66PT-1/2 | 30915 | — | 1/2 | 12.7 | 5/16 | 7.9 | .7 | 318 |
| • | 66PT5/8 | 30919 | _ | 5/8 | 1/2 12.7 5/16 5/8 15.9 7/16 11/16 17.5 7/16 3/4 19.1 7/16 13/16 20.6 7/16 15/8 22.2 7/16 15/16 23.8 7/16 15/16 23.8 7/16 1 25.4 7/16 1/8 28.6 7/16 | 11.1 | .8 | 363 | |
| | 66PT-11/16 | 30921 | _ | 11/16 | 17.5 | 7/16 | 11.1 | 1 | 454 |
| | 66PT-3/4 | 30923 | 36659 | 3/4 | 19.1 | 7/16 | 11.1 | 1.2 | 545 |
| | 66PT-13/16 | 30925 | _ | 13/16 | 20.6 | 7/16 | 11.1 | 1.2 | 545 |
| | 66PT7/8 | 30927 | 36662 | 7/8 | 22.2 | 7/16 | 11.1 | 1.5 | 681 |
| | 66PT-15/16 | 30929 | _ | 15/16 | 23.8 | 7/16 | 11.1 | 1.6 | 726 |
| | 66PT-1 | 30931 | 36664 | 1 | 25.4 | 7/16 | 11.1 | 1.8 | 817 |
| | 66PT-1-1/8 | 30935 | | 1/8 | 28.6 | 7/16 | 11.1 | 2.3 | 1044 |
| | 66PT-1-1/4 | 30937 | _ | 1-1/4 | 31.8 | 7/16 | 11.1 | 2.8 | 1270 |
| | | | | | | | | | |

- · Quickly bore through creosoted and salt-treated utility poles
- Resists wear, eats through nails and staples •
- Self-feeding screw point draws the bit through the wood •
- 7/16" hex shank to fit impact drivers
- Available in 18" overall length

NAIL EATER® EXTREME

| | | HARD | NARE | HOLE | | OVERALL | | HEX | | | | |
|---------|---------|----------|------|------|----------|---------|--------|------|-------|-----|--------|--|
| | POP | DIAMETER | | DIAM | DIAMETER | | LENGTH | | SHANK | | WEIGHT | |
| CAT. NO | UPC NO. | INCH | MM | INCH | MM | INCH | MM | INCH | ММ | LBS | G | |
| 37868 | 37868 | 9/16 | 14.3 | 5/8 | 15.9 | 18 | 457.2 | 7/16 | 11.1 | 0.9 | 409 | |
| 37869 | 37869 | 11/16 | 17.5 | 3/4 | 19.1 | 18 | 457.2 | 7/16 | 11.1 | 1.1 | 499 | |
| 37870 | 37870 | 13/16 | 20.6 | 7/8 | 22.2 | 18 | 457.2 | 7/16 | 11.1 | 1.4 | 636 | |
| 37871 | 37871 | 15/16 | 23.8 | 1 | 25.4 | 18 | 457.2 | 7/16 | 11.1 | 1.5 | 681 | |