



## Reciprocating Saw Blades

	CAT. NO.	LENGTH X WIDTH X THICKNESS INCH / MM	MATERIAL	QTY/ PK	TEETH PER INCH	SPEED AND QUALITY OF CUT
<b>BI-METAL</b>						
<b>NOTE:</b> Minimum blade length = Material width + 3"						
	353-624	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for sheet metal (1/8" and less).	5	24T	SLOWER, SMOOTHER ↑ ↓ FASTER, ROUGHER
	353-818	8 x 3/4 x .035 / 203 x 19 x .9	<b>BETTER</b> for thin metal (1/16" - 3/16").	5	18T	
	353-618	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for thin metal (1/16" - 3/16").	5	18T	
	353-814	8 x 3/4 x .050 / 203 x 19 x 1.3	<b>BETTER</b> for medium metal (3/32" - 3/8").	5	14T	
	353-614	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for medium metal (3/32" - 3/8").	5	14T	
	353-414	4 x 3/4 x .035 / 102 x 19 x .9	<b>BETTER</b> for medium metal (3/32" - 3/8").	5	14T	
	353-804	8 x 3/4 x .050 / 203 x 19 x 1.3	<b>BETTER</b> for thick metal (1/8" - 1/2").	5	10/14T	
	353-835	8 x 3/4 x .035 / 203 x 19 x .9	<b>BETTER</b> for general purpose.	5	10/14T	
	353-635	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for general purpose.	5	10/14T	
	353-110	12 x 3/4 x .050 / 305 x 19 x 1.3	<b>BETTER</b> for general purpose.	5	10/14T	
	353-810	8 x 3/4 x .050 / 203 x 19 x 1.3	<b>BETTER</b> for general purpose.	5	10T	
	353-610	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for general purpose.	5	10T	
	353-123	6 x 3/4 x .035 / 152 x 19 x .9	<b>BETTER</b> for general purpose.	5	8/18T	
	353-969	9 x 7/8 x .063 / 229 x 22 x 1.6	<b>BEST</b> for demolition projects.	5	8/10T	
	353-646	6 x 3/4 x .050 / 152 x 19 x 1.3	<b>BETTER</b> for clean wood and wood with nails.	5	6T	
	353-656	6 x 3/4 x .050 / 153 x 19 x 1.3	<b>BETTER</b> for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-956	9 x 3/4 x .050 / 229 x 19 x 1.3	<b>BETTER</b> for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-156	12 x 3/4 x .050 / 305 x 19 x 1.3	<b>BETTER</b> for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-636	6 x 3/4 x .050 / 152 x 19 x 1.3	<b>BETTER</b> for drywall and plaster.	5	6T	
<b>SPECIALTY</b>						
<b>NOTE:</b> Minimum blade length = Material width + 3"						
	353-800RDG	8 x 3/4 x .039 / 203 x 19 x 1	<b>BEST</b> for cast iron pipe, block & brick and other abrasives such as tile.	1	Diamond Grit	SLOWER, SMOOTHER ↑ ↓ FASTER, ROUGHER
	353-618RS	6 x 3/4 x .039 / 152 x 19 x 1	<b>BEST</b> for stainless steel (1/16" - 3/16"). Carbide teeth	1	18T	
	353-6563RCT	6 x 3/4 x .050 / 152 x 19 x 1.3	<b>BEST</b> for cement board, fiber board, and plaster. Carbide tipped	1	6T	