# **CEILING BOXES AND COVERS**

## CEILING FAN AND FIXTURE SUPPORT PRODUCTS

#### **APPLICATION**

 GRID-BRACE<sup>™</sup> ceiling support assembly is specifically designed for ceiling fan or fixture support for suspended ceilings

#### **PRODUCT FEATURES**

- Heavy-duty GRID-BRACE<sup>™</sup> for 24" spans
- Turnbuckle and 4' chain section provided
- Yoke provided for threaded rod installation
- Mount box anywhere on sliding bracket
- Spacers provided for decorative ceiling tiles that are below the depth of metal grid for flush mounting of box →
- #10-32 grade 5, 1" ceiling fan screws included
- · Easy to follow instructions included



CAT.#	DESCRIPTION	CUBIC INCHES (CM3)		KNOCKOUTS	RECOMMENDED MAX. LOADS		CTD	BAR		
			SIDES	BOTTOM CONDUIT	CEILING FAN (Dynamic) LBS.	FIXIUKE	DKC	CODE		
GRID-BRACE™ For Suspended Ceilings, 2-1/8" Deep										
<i>NEW</i> 931	Ceiling Fan Support for Suspended Ceilings	22.3 (365.4)	(2) 1/2"	(2) Conc. 1/2" & 3/4"	70	70	4			

#### CEILING PANS

#### **APPLICATION**

 RACO® Ceiling Pans are used in the installation of ceiling or wall lighting fixtures

### **PRODUCT FEATURES**

 Combination screw heads provide for faster installation

#### **COMPLIANCE**

• **U** File E195978

U.S. Patent 7,148,420, 4,892,211 Canada 1,324,360 Mexico 166,125



292, 8292



287



293, 8293

	DESCRIPTION	CUBIC INCHES (CM3)	KNOCKOUTS			RECOMMENDED MAX. LOADS		CTD	DAD		
CAT.#			CABLE Priouts	SIDES Conduit	BOTTOM Conduit	CEILING FAN (DYNAMIC) LBS.	FIXTURE (STATIC) LBS.	STD. BAI PKG. COD	CODE		
3-1/2" Round Ceiling Pan — Drawn with Nonmetallic Sheathed Cable Clamps											
292	1/2" Depth	4.0 (65.5)	4	_	(1) 1/2"	No	50	50			
8292	1/2" Depth	4.0 (65.5)	4	_	(1) 1/2"	No	50	25			
287	3/4" Depth	5.0 (81.9)	4	_	(1) 1/2"	No	50	50	—		
4" Round Ceiling Pan — Drawn with Conduit KO's											
293	1/2" Depth	6.0 (98.3)	_	_	(5) 1/2"	No	50	50	_		
8293	1/2" Depth	6.0 (98.3)	_	_	(5) 1/2"	No	50	50	IIIIIIII		