RA GO

4" OCTAGON BOXES - DRAWN WITH ARMORED CABLE / METAL CLAD / FLEX CLAMPS

APPLICATIONS

 RACO® Octagon Boxes are used in the installation of ceiling or wall lighting fixtures

PRODUCT FEATURES

- RACO® offers a variety of labor saving mounting brackets that allow for easy positioning of box along studs or joists
- Reference the Box Selection section in the front of this catalog for complete description of bracket types and features
- Fixture bar hanger allows box to be located anywhere along length of bar

COMPLIANCE

• (I) File E195978




		CUBIC	KNOCKOUTS			RECOMMENDED MAX. LOADS		STD.	DAD
CAT. #	DESCRIPTION	INCHES (CM3)	CABLE Priouts	SIDES Conduit	BOTTOM Conduit	CEILING FAN (DYNAMIC) LBS.	FIXTURE (STATIC) LBS.	DKC	CODE
4" Octagon Box, 1-1/2" Deep — Drawn with Armored Cable/Metal Clad/Flex Clamps									
153	_	15.5 (254.0)	4	(2) 1/2"	(1) 1/2"	No	50	25	11111111
155	TS Bracket, 1/2" Setback	15.5 (254.0)	4	(1) 1/2"	(1) 1/2"	No	50	50	
157	J Bracket, 3/8" or 1/2" Setback	15.5 (254.0)	4	(2) 1/2"	(1) 1/2"	No	50	50	
325	Box with 14-1/4" to 22-1/2" bar hanger	15.5 (254.0)	4	(2) 1/2"	_	No	10*	25	_
8325	Box with 14-1/4" to 22-1/2" har hanger	15.5 (254.0)	4	(2) 1/2"	_	No	10*	25	11111111

^{* 10} lbs max. load recommended. UL Rated for 50 lbs on 16" centers.




OCTAGON BOXES

3-1/2" OCTAGON BOXES




CAT. #	DIMENSIONS							
UA1. #	A (INSIDE)	В	C	D	E			
110	1-1/2"	3-1/2"	-	-	-			
111	1-1/2"	3-1/2"	-	-	-			
112	1-1/2"	3-1/2"	-	-	-			
119	1-1/2"	3-1/2"	7"	-	1-1/16"			

4" OCTAGON CABLE BOXES



CAT #	DIMENSIONS							
CAT. #	A (INSIDE)	В	C	D	E	F		
145	1-1/2"	4"	-		-	-		
146	1-1/2"	4"	1	-	-	-		
150	1-1/2"	4"	-	-	-	-		
153	1-1/2"	4"	1	-	-	-		
155	1-1/2"	4"	7"	1/2"	1-1/16"	-		
157	1-1/2"	4"	2-3/8"	-	-	3-1/8"		
160	1-1/2"	4"	2-3/8"	-	-	3-1/8"		
164	1-1/2"	4"	7"	1/2"	1-1/16"	-		
175	2-1/8"	4"	-	-	_	-		
176	2-1/8"	4"	2-3/8"	5/8"	-	3-3/4"		
177	2-1/8"	4"	7"	1/2"	1-1/16"	-		

4" OCTAGON CONDUIT BOXES



CAT. #	DIMENSIONS							
GAI.#	A (INSIDE)	В	C	D	E	F		
125, 8125	1-1/2"	4"	-	-	-	-		
126	1-1/2"	4"	-	-	-	-		
127	1-1/2"	4"	-	-	-	-		
127TS	1-1/2"	4"	7"	1/2"	1-1/16"	-		
128	1-1/2"	4"	-	-	-	-		
130	1-1/2"	4"	-	-	-	-		
131RAC	1-1/2"	4"	-	-	-	-		
158	1-1/2"	4"	2-3/8"	-	-	3-1/8"		
165	2-1/8"	4"	-	-	-	-		
166	2-1/8"	4"	-	-	-	-		
161	1-1/2"	4"	7"	1/2"	1-1/16"			
167	2-1/8"	4"	-	-	-	-		
167TS	2-1/8"	4"	7"	1/2"	1-1/16"	_		