
4 IN. SQUARE WELDED BOXES - 1-1/2 TO 2-1/8 IN. DEEP WITH NONMETALLIC SHEATHED CABLE CLAMPS

4 in. Square Boxes, 2-1/8 in. Deep - Welded with Nonmetallic Sheathed Cable Clamps







Catalog #: 240

APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices

PRODUCT FEATURES

Reference the Box Selection section in the front of this catalog for complete description of bracket types and features

Combination screw heads provide for faster installation TKO® Knockouts offer greater flexibility with RACO patented combination 1/2" and 3/4" knockout

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Nonmetallic Sheathed Cable Wiring System:

Country of Origin: USA

CONFIGURATION

Cable Priouts

Bracket Type: TS, for Metal or Wood Studs

Bracket Setback: Drawn or Welded: Welded Raised Ground:

(2) 1/2 in. & (1) TKO® Side Knockout(s):

(1) 1/2 in. Bottom Knockouts(s):

DRAWING DIMENSIONS

2-1/8 in. Dimension A: Dimension B 7 in. 4-5/16 in. Dimension C:

PRODUCT MEASUREMENTS

Depth: 2-1/8 in Cubic Inches (cm3): 30.3 (496.5) Wt. Ea. (Lbs.): 1.066 Product Length (in.): Product Width (in.): 2.188 4.313 Product Height (in.):

PACKAGING

Minimum Pack Qty.: Std. Pkg.: 25 25 Product UPC-A Labeled: Weight (Lbs. Per/C): Ship Carton Length (in.): 106.6 20.875 Ship Carton Width (in.): Ship Carton Height (in.): 9 8.5 Ctn Weight (Lbs.): 26.65 Pallet Qty: UPC Number: 1375

050169902400 12of5 50050169902405