
SINGLE DEVICE HANDY BOXES & EXTENSION RINGS

4 in. x 2 in. Handy Boxes, 1-7/8 in. Deep - Drawn with Conduit KO's

A44





Catalog #: 660

APPLICATIONS

RACO® Handy boxes, also called utility boxes, are used for convenience outlets, switch boxes or small junction boxes

They are popular for exposed work applications (surface mounted wiring)

The NEC requires that surface-mounted wiring be enclosed with a protective covering such as EMT conduit

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

CSA

GENERAL PRODUCT INFORMATION

Wiring System: Conduit Country of Origin: USA

CONFIGURATION

End Knockouts: (2) 1/2 in. Bracket Type: Drawn or Welded: No Bracket Drawn Raised Ground: Side Knockout(s): Yes (6) 1/2 in. Bottom Knockouts(s): (2) 1/2 in.

DRAWING DIMENSIONS

Dimension A: 1-7/8 in.

PRODUCT MEASUREMENTS

Depth: 1-7/8 in Cubic Inches (cm3): 13.0 (213.0) 0.48 Wt. Ea. (Lbs.): Product Length (in.): 1.938 Product Width (in.): Product Height (in.): 2.125

PACKAGING

Minimum Pack Qty.: 50 Std. Pkg.: Product UPC-A Labeled: 50 No Weight (Lbs. Per/C): Ship Carton Length (in.): Ship Carton Width (in.): 48 11.125 8.5 Ship Carton Height (in.): Ctn Weight (Lbs.): 10 24 Pallet Qty: UPC Number: 4000

050169906606 50050169906601 12of5: