



Magnuliter® Floodlight MV Series

QS7 10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 15

MV SERIES — Vertical lamp position. Features wide, uniform beam distribution. (Coverage is four times set back distance)

CATALOG NUMBER	MOUNT	PHOTOMETRY NEMA/IES H° X V°	WATTAGE	WEIGHT LBS. (KG)	EPA FT ² (M ²)
MVM-0400P-265	Trunnion mount, Bronze	7(146°) x 6(119°)	400 PSMH	41 (18.6)	2.3 (.22)
MVM-0400P-268	Trunnion mount, Bronze	7(146°) x 6(119°)	400 PSMH	41 (18.6)	2.3 (.22)
MVK-0400S-268	Slipfitter mount, Bronze	7(144°) x 6(113°)	400 HPS	43 (19.5)	2.3 (.22)



Laramie® Floodlight LFL Series

3S SCHEDULED STOCK SHIPMENTS
Regional Distribution Center Stock List

Part Number	Catalog Number	UPC Code	Description	CA 03	IL 06	PA 10	SC 07	TX 04	Wt. each	Ctn. Qty.	Price
LFLY1000HVW8BZ	LFL-Y-1000HV-W8-BZ	785988018826	Flood, Yoke, 1000w MH, Quad-Tap, Wide beam, Bronze		•				48.0	EA	



LNC LED Wallpacks



3S SCHEDULED STOCK SHIPMENTS
Regional Distribution Center Stock List

Part Number	Catalog Number	UPC Code	Description	CA 03	IL 06	PA 10	SC 07	TX 04	Wt. each	Ctn. Qty.	Price
LNC5LU5K	LNC-5LU-5K	785988020645	Wallpack, Full cut-off, LNC, 13w LED, 120-277V, Bronze	•	•	•	•	•	4.0	EA	
LNC5LU5KPC	LNC-5LU-5K-PC	785988020652	Wallpack, Full cut-off, LNC 13w LED, 120V,, PC , Bronze	•	•	•		•	4.0	EA	
LNC7LU5K31	LNC-7LU-5K-3-1	785988020669	Wallpack, Full cut-off , LNC, 16w LED, 120-277V, 5K, Type III, Bronze	•	•	•		•	4.0	EA	
LNC9LU5K31	LNC-9LU-5K-3-1	785988020683	Wallpack, Full cut-off , LNC, 21w LED, 120-277V, 5K, Type III, Bronze	•	•	•		•	4.0	EA	

QS5 5-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 15

CATALOG NUMBER	DESCRIPTION	CCT	WT. EACH	LUMENS	WATTS
LNC-7LU-5K-3-1-PC1	Wallpack, Full cut-off , LNC, 16w LED, 120-277V, 5K, Type III, Bronze, Photocontrol	5000K	4.0	1140	16
LNC-9LU-5K-3-1-PC1	Wallpack, Full cut-off , LNC, 21w LED, 120-277V, 5K, Type III, Bronze, Photocontrol	5000K	7.0	1460	21

QS7 10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 15

LNC	-		-	5K	-		-		-	
SERIES	NUMBER OF LEDS/SOURCE/VOLTAGE	CCT	IES DISTRIBUTION	FINISH	OPTIONS					
LNC LNC no uplight	7LU 7 LEDs, up to 1147 lumens, 16.4w input, 120-277V 9LU 9 LEDs, up to 1460 lumens, 20.6w input, 120-277V	5K 5000K nominal	3 Type III 4 Type IV	1 Bronze 2 Black 4 White 5 Platinum	PC(X) Button photo-control, replace X with voltage, specify 1-120V, 2-208V, 3-240V, 4-277V					