

MAGNUDISC™ II MEDIUM

Cat. #		Approvals
Job	Type	

**SPAULDING
LIGHTING**

APPLICATIONS

- Designed to meet the complex lighting needs of leading corporate office parks, retailers and restaurants.


SPECIFICATIONS

- Spun aluminum two-piece, flat or dome style which totally encloses electrical and optical assemblies; Rigid design with galvanized steel Powr-Panl®
- Convex glass lens allows high angle illumination for wide spacing and greater uniformity while the flat glass provides sharp IESNA full cut-off to reduce light trespass; Multi-piece segmented reflector systems for excellent performance; Tool-free rotatable optics
- Durable Lektrocote® TGIC thermo-set polyester powder paint with a textured finish assures long life and maintenance-free service

- Units are available in arm, vertical spoke (post top), single and double horizontal spoke and wall mount; The arm is extruded aluminum; Spoke mount assemblies allow luminaire to be tilted in the field
- HPF Quad-Tap® or Tri-Tap®; All components mounted on galvanized Powr-Panl® which easily installs without tools; Fusing and photocontrol options available; For 50Hz ballasts, consult factory

LISTINGS/CERTIFICATIONS

- Listed to UL1598 for use in wet locations
- IESNA full cut-off classification when configured with flat lens



NOTE: arm mounting also available

	A	B	C	D	E	EPA	Weight
DS	25"	14 1/8"	10 1/4"	23 1/4"	19 3/4"	1.7 ft²	63 lbs.
SPOKE	635 mm	359 mm	254 / 102 mm	590 mm	502 mm	0.2 m²	28.5 kg

- Note: Arm mounting also available
- Note: DMS arm mount EPA = 1.59 ft² (luminaire only)
DMF arm mount EPA = 1.7 ft² (luminaire only)
- Note: Convex lens adds 0.1 ft² EPA



ORDERING INFORMATION

ORDERING EXAMPLE: DS-F-D-150S-1-P-8-DB-DB-F1

DM	-		-		-		-		-		-		-	
SERIES														
DM Magnudisc Medium (250-400w)														
STYLE														
F Flat S Dome														
MOUNT														
A ³ Arm mount (arm not included, order separately) D ⁴ Spoke - vertical F ⁴ Spoke - horizontal (single) G ⁴ Spoke - horizontal (double - 180°) K Wall/spoke														
WATTAGE/SOURCE														
PULSE START METAL HALIDE 250P 250w (ED-28) 400P ⁷ 400w (ED-37) HIGH PRESSURE SODIUM 000S No ballast 250S 250w (ED-18) 400S 400w (ED-18)														
CONSTRUCTION														
H ⁵ Horizontal lamp V ⁶ Vertical lamp														
OPTICS														
I Type I P ¹ Type III T Type IV W Type V														
VOLTAGE														
8 ² Quad-Tap® 120/208/240/277V 5 480V 6 ² Tri-Tap® 120/277/347V E 220/240V, 50Hz 0 No ballast														
SPOKE COLOR (req'd for spoke mount only)														
DB Dark Bronze BL Black WH White GR Gray PS Platinum Silver RD Red (premium color) FG Forest Green (premium color)														
COLOR														
1 Dark Bronze 2 Black 4 White 3 Gray P Platinum Silver R Red (premium color) 7 Forest Green (premium color)														
OPTIONS														
F(X) Fusing (replace X with voltage: 1-120, 2-208, 3-240, 4-277, 5-480, 6-347) PC(X) Photo button (replace X with voltage: 1-120, 2-208, 3-240, 4-277, 6-347) LD Convex lens for horizontally lamped units L Lamp														
MOUNTING ARM (order separately)														
MAL-4-X 4" rigid arm for flat surfaces MAL-10-X 10" rigid arm for flat surfaces RSD-04-X Nominal 4" OD round pole adapter for MAL arms RSD-05-X Nominal 5" OD round pole adapter for MAL arms MAL-WP-X Wall plate for flat surfaces Note: Replace X with color selection														

1 Field adjustable to Type II
2 Factory wired for highest voltage unless specified
3 DM arm mount - use #6 drill pattern when ordering poles
4 DM spoke mount requires 2 3/8" tenon top pole
5 Flat glass standard
6 Convex lens only; ED-28 lamp included with 400w PSMH
7 DM with vertical lamp orientation includes 400w PSMH ED-28 lamp

NOTE: Use #6 drill pattern when ordering poles.

ORDERING INFORMATION

ACCESSORIES (Must be ordered separately. For field installation.)


Catalog Number	Description
DS ACCESSORIES	
MAS-4-X^{1,4}	4" Rigid Arm for flat surfaces (0.12 ft ² EPA)
MAS-10-X^{1,4}	10" Rigid Arm for flat surfaces (0.31 ft ² EPA)
RSD-44-X^{1,4}	Nominal 4" OD Round Pole Adapter for MAS arms
RSD-55-X^{1,4}	Nominal 5" OD Round Pole Adapter for MAS arms
DS-WP-X¹	Wall Plate for flush or arm mounting fixtures with #4 drill pattern
DM ACCESSORIES	
MAL-4-X^{2,3}	4" Rigid Arm for flat surfaces
MAL-10-X^{2,3}	10" Rigid Arm for flat surfaces
RSD-04-X^{2,3}	Nominal 4" OD Round Pole Adapter for MAL arms
RSD-05-X^{2,3}	Nominal 5" OD Round Pole Adapter for MAL arms
MAL-WP-X²	Wall Plate for flat surfaces with #6 drill pattern
SSS-490-XX²	Square Pole Tenon Adapter (4 @ 90°) (2 ³ / ₈ " -2 ⁷ / ₈ " OD tenon)
RSS-490-XX²	Round Pole Tenon Adapter (4 @ 90°) (2 ³ / ₈ " -2 ⁷ / ₈ " OD tenon) (requires 4" round pole adapter)
RSS-3120-XX²	Round Pole Tenon Adapter (3 @ 120°) (2 ³ / ₈ " -2 ⁷ / ₈ " OD tenon) (requires 4" round pole adapter)

1 DS luminaire only.


2 DM luminaire only.

3 DM arm mount - use #6 drill pattern when ordering poles.


4 DS arm mount - use #4 drill pattern when ordering poles.



MAS-XX-X / MAL-XX-X



DS-WP-X



**RSD-04/05-X
RSD-44/55-X**



MAL-WP-X

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

SPAULDING
LIGHTING

Spaulding Lighting • 701 Millennium Drive • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: www.spauldinglighting.com