



A.

K1100, K1200 Series Relay-Type Photo Controls with Locking-Type or Adjustable-Stem Mounting



- Instant ON/OFF switching with two mounting types
- K1100 models have three 6" color-coded leads
- K1200 models have 2400 volt open-type spark gap arrester and standard 3-prong connector
- Adjustable stem models can be set at any angle up to 80 degrees
- 2-year warranty

Adjustable Stem

Model #	Voltage	Amps Tungsten	Amps Ballast
A. K1121	105-130 VAC, 50/60 Hz	15	15
K1122	208-240 VAC, 50/60 Hz	7.5	7.5

Twist Lock

Model #	Voltage	Amps Tungsten	Amps Ballast
B. K1221	105-130 VAC, 50/60 Hz	15	8.3
K1222	208-240 VAC, 50/60 Hz	7.5	7.5

Rating:

Watts Tungsten: 1800

VA Ballast: 1800

Activation: 1 FC ON, 3 – 10 FC OFF

Operating Temperature: -40°F to 158°F (-40°C to 70°C)

Dimensions: K1100 Series: 5 3/4" (14.6 cm) H x 3" (7.6 cm) Ø, 1/2" – 14 NPT Stem

K1200 Series: 3 3/4" (9.5 cm) H x 3" (7.6 cm) Ø



B.



C.

LC2000



Low Cost Relay-Type Photo Control with Locking-Type Mounting

- Complies with ANSI C136.10 Standard
- Easy-to-install plug-in locking-type connector
- Heavy-duty relay designed for long life switching
- Instant ON/OFF switching
- 2-year warranty

Model #	Voltage	Watts Tungsten	VA Ballast
C. LC2000	110-277 VAC, 50/60 Hz	1000	1800

Rating:

Activation: 1 to 3 FC ON, Turn OFF to turn ON ratio is 4

Dimensions: 2 3/8" (5.6 cm) H x 3 3/16" (8.1 cm) Ø