



## EI600 and ST01 Series

### Heavy-Duty 7-Day Programmable Timers

Highly versatile Heavy-Duty Timers are ideal for any application that requires a simple or complex ON/OFF schedule, regardless of load. No neutral connection is required.

#### Features

- Versatile 7-day programmable schedules with up to 40 ON/OFF events
- Astronomic clock feature determines dawn and dusk times
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Isolated switch allows timer to be used with any load type, including AC and DC loads
- Replaceable CR2 lithium battery provides up to three years of operation
- No neutral wire connection enables easy retrofitting and quicker installation



Ratings	
<b>Operating Voltage</b>	120-277 VAC, 50/60 Hz
<b>Resistive</b>	
ST01	15 A, 120-277 VAC, 50/60 Hz
EI600	20 A, 120-277 VAC, 50/60 Hz
<b>Inductive Ballast</b>	
ST01	8 A, 120 VAC, 50/60 Hz; 4 A, 208-277 VAC, 50/60 Hz
EI600	16 A, 120-277 VAC, 50/60 Hz
<b>Incandescent</b>	15 A, 120 VAC, 50/60 Hz; 6 A, 208-277 VAC, 50/60 Hz
<b>Motor</b>	1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz
<b>DC Loads</b>	4 A, 12 VDC; 2 A, 28 VDC
<b>Operating Temperature</b>	32° F to 104° F (0° C to 40° C)
<b>Dimensions H x W x D</b>	4.125" X 1.75" X 1.8125" (104.8mm x 44.5mm x 46mm)
<b>Warranty</b>	
ST01	1-year limited
EI600	5-year limited

White	Ivory	Light Almond	Max Load Handling Capability
<b>EI600WC</b>	<b>EI600C</b>	<b>EI600LAC</b>	20 A
<b>ST01</b>	–	<b>ST01A</b>	15 A

Note: For use with standard decorator plate, not included

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

## 7-Day/24-Hour Timer Applications

- Entryway lighting • Deck and landscape light controls • Attic fans • Pumps
- Small commercial – signage and store lighting • Hallway lighting

