

EI500 Series

Standard 7-Day Programmable Timers - 15 A

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads.

Features

- 7-day programmable schedules with 14 ON/OFF events
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single-pole circuit
- Incandescent/fluorescent/CFL/LED compatible
- Built-in rechargeable, non-serviceable battery backup
- Requires neutral connection
- Backlit LCD display

White	Ivory	Light Almond
EI500WC	EI500C	EI500LAC

Note: For use with standard decorator plate, not included.



White



Ivory



Light Almond



EI500WC



Ratings	
Operating Voltage	125 VAC, 60 Hz
General Purpose	15 A, 125 VAC, 60 Hz
Resistive	15 A, 125 VAC, 60 Hz
Inductive Ballast (Fluorescent)	1000 VA, 125 VAC, 60 Hz
Electronic/LED Ballast	500 VA, 125 VAC, 60 Hz
Incandescent	1000 W, 125 VAC, 60 Hz
Motor	¼ HP, 125 VAC, 60 Hz
Operating Temperature	32° F to 104° F (0° C to 40° C)
Dimensions H x W x D	4.125" X 1.75" X 1.4375" (104.8 mm x 44.5 mm x 36.5 mm)
Warranty	1-year limited

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

EJ600 Series

Standard 7-Day Programmable Timers - 12 A

A 12 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads.

Features

- 7-day programmable schedules with 7 ON/OFF events
- Astronomic clock feature determines dawn and dusk times
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Built-in rechargeable, non-serviceable battery backup
- Requires neutral connection

White	Light Almond
EJ600	EJ600A

Note: For use with standard decorator plate, not included.



White



Light Almond



EJ600



Ratings	
Operating Voltage	120 VAC, 60 Hz
Resistive	12 A, 120 VAC, 60 Hz
Inductive Ballast	500 VA, 120 VAC, 60 Hz
Incandescent	
Single-Gang	15 A, 120 VAC, 60 Hz
Multi-Gang	12 A, 120 VAC, 60 Hz
Motor	½ HP, 120 VAC, 60 Hz
Operating Temperature	32° F to 104° F (0° C to 40° C)
Dimensions H x W x D	4.125" X 1.75" X 1.4375" (104.8 mm x 44.5 mm x 36.5 mm)
Warranty	1-year limited

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.