

THREAD SEALANTS

**TYTE-UNYTE®** Non-hardening Gray Pipe Joint Compound in paste form. No Drip, Thixotropic Formula. For Air, Steam, Natural Gas and Water. "Standard of the Industry Since 1900." For use on all metal threads. Meets Federal Specification TT-A-580D. **MADE IN THE U.S.A.**

STOCK CODE	SIZE	CONTAINER	ITEMS/CASE	CASE WEIGHT	LIST PRICE EACH
<b>T2</b>	2 oz. - .056 kg	Tube**	72	10 lbs. - 4.5 kg	1.80
<b>T4</b>	1/4 Pint/1/2 lb. - .227 kg	Brush Top Can	24	17 lbs. - 7.7 kg	3.20
<b>T8</b>	1/2 Pint/1 lb. - .454 kg	Brush Top Can	24	26 lbs. - 11.8 kg	4.67
<b>T16</b>	Pint/2 lbs. - .92 kg	Brush Top Can	12	25 lbs. - 11.3 kg	7.11
<b>T6</b>	6 lbs. - 2.72 kg	Pail w/Handle	4	31 lbs. - 14.1 kg	15.29
<b>T14</b>	14 lbs./Gal. - 6.35 kg	Can w/Handle	4	60 lbs. - 27.2 kg	35.84
<b>T50</b>	50 lbs./5 Gal. - 22.68 kg	Pail w/Handle	1	54 lbs. - 24.5 kg	142.27
<b>T600</b>	600 lbs./55 Gal. - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg	1377.93



**STEEL-UNYTE** Pipe Joint, Thread and Gasket Sealer. Hard-Set, dark gray, semi-paste for use on all Metal Threaded Connections and Flanges. Meets Military Specification MIL-S-7916B. **MADE IN THE U.S.A.**

<b>ST8</b>	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg	11.42
<b>ST8A</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	11 lbs. - 5.0 kg	12.44
<b>ST16</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	18.40
<b>ST32</b>	Quart - .95 L	Brush Top Can	12	43 lbs. - 19.5 kg	29.20
<b>ST1</b>	Gallon - 3.785 L	Can w/Handle	4	46 lbs. - 20.9 kg	98.09
<b>ST5</b>	5 Gallon - 18.9 L	Pail w/Handle	1	65 lbs. - 29.5 kg	401.89
<b>ST55</b>	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg	1255.47



**T-U TYPE 555** Soft-Set, Yellow Thread Sealing Compound for use on Plastic and Metal Threaded Systems carrying Air, Steam, Petroleum, Water, Gases and many Chemicals. Meets Federal Specification TT-S-1732. **MADE IN THE U.S.A.**

<b>TU4</b>	1/4 Pint - 118 ml	Brush Top Can	24	14 lbs. - 6.4 kg	6.96
<b>TU8</b>	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg	12.24
<b>TU8A</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	11 lbs. - 5.0 kg	13.38
<b>TU16</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	19.64
<b>TU32</b>	Quart - .95 L	Brush Top Can	12	41 lbs. - 18.6 kg	35.93
<b>TU1</b>	Gallon - 3.785 L	Can w/Handle	4	53 lbs. - 24.0 kg	107.36
<b>TU5</b>	5 Gallon - 18.9 L	Pail w/Handle	1	65 lbs. - 29.5 kg	451.42
<b>TU55</b>	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg	3874.24



**BLUE MAGIC** All Purpose, Non-seizing, Industrial Grade Pipe Thread Compound that produces a leakproof seal on all types of Metal and Plastic Threaded Connections. Suitable for ABS, PVC, CPVC, and BlazeMaster® Threaded Connections. Meets Federal Specification TT-S-1732. **MADE IN THE U.S.A.**

<b>IG2</b>	2 oz. - .056 kg	Tube**	72	11 lbs. - 5.0 kg	3.71
<b>IG4</b>	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg	7.18
<b>IG8</b>	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg	11.36
<b>IG8A</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg	12.33
<b>IG16</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	18.80
<b>IG32</b>	Quart - .95 L	Brush Top Can	12	42 lbs. - 19.1 kg	33.73
<b>IG1</b>	Gallon - 3.785 L	Can w/Handle	4	53 lbs. - 24.0 kg	103.98
<b>IG5</b>	5 Gallon - 18.9 L	Pail w/Handle	1	65 lbs. - 29.5 kg	423.71
<b>IG55</b>	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg	3820.64
<b>IG8C*</b>	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg	11.36
<b>IG8CA*</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg	12.33
<b>IG16C*</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	18.80



**SELECT-UNYTE** Soft-Set, White All Purpose PTFE Paste Thread Sealing Compound. For use on Plastic and Metal Threaded Systems carrying Air, Steam, Petroleum, Water, Gases and many Chemicals. Meets Federal Specification TT-S-1732. **MADE IN THE U.S.A.**

<b>TF2</b>	2 oz. - .056 kg	Tube**	72	11 lbs. - 5.0 kg	3.91
<b>TF4</b>	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg	7.07
<b>TF8</b>	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg	12.69
<b>TF8A</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg	13.93
<b>TF16</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	20.93
<b>TF32</b>	Quart - .95 L	Brush Top Can	12	43 lbs. - 19.5 kg	38.40
<b>TF1</b>	Gallon - 3.785 L	Can w/Handle	4	52 lbs. - 23.6 kg	117.22
<b>TF5</b>	5 Gallon - 18.9 L	Pail w/Handle	1	66 lbs. - 29.9 kg	484.67
<b>TF55</b>	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg	4231.13
<b>TF8C*</b>	1/2 Pint - 237 ml	Brush Top Can	24	23 lbs. - 10.4 kg	12.69
<b>TF8CA*</b>	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg	13.93
<b>TF16C*</b>	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg	20.93
<b>TF32C*</b>	Quart - .95 L	Brush Top Can	12	43 lbs. - 19.5 kg	38.40



**POWER SEAL PLUS** Non-Drying, Arctic Blue PTFE Based Thread Sealing Compound. Specially formulated for the Fire Sprinkler Industry for use on all Metal Threaded Connections, FlowGuard Gold®, BlazeMaster®, and Corzan® CPVC pipe and fittings. Meets Federal Specification TT-S-1732. **MADE IN THE U.S.A.**

<b>POW16</b>	Pint - 473 ml	Flat Top Can	12	24 lbs. - 10.9 kg	21.89
<b>POW16B</b>	Pint - 473 ml	Brush Top Can	12	24 lbs. - 10.9 kg	21.89
<b>POW32</b>	Quart - .95 L	Plastic Container w/Twist Top Lid	12	42 lbs. - 19.1 kg	40.11
<b>POW32B</b>	Quart - .95 L	Brush Top Can	12	44 lbs. - 20.0 kg	40.11
<b>POW1</b>	Gallon - 3.785 L	Can w/Handle	4	60 lbs. - 27.2 kg	122.53
<b>POW5</b>	5 Gallon - 18.9 L	Pail w/Handle	1	51 lbs. - 23.1 kg	509.53
<b>POW55</b>	55 Gallon - 208 L	55 Gallon Drum	1	740 lbs. - 335.7 kg	4480.13



\*Bilingual Label: French and English. \*\*Tubes Packed 12 Per Clear Plastic Tub. FlowGuard Gold®, BlazeMaster®, and Corzan® are Registered Trademarks of Lubrizol. Pallet Quantities for Thread Sealants: 1/4 Pint = 130 Cases, 1/2 Pint = 80 Cases, 1 Pint = 80 Cases, 1 Quart = 56 Cases, 1 Gallon = 45 Cases.